


F-PP

FLAT TIP TERMINAL, PRE-INSULATED WITH PVC, FOR COPPER CONDUCTORS



CERTIFICATIONS & APPROVALS

UL (cULus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-20 °C
Maximum operating temperature	75 °C
Threshold of operating temperature for short periods	90 °C
Bend angle of the connection	0 °
Barrel reinforcement ring	No
Markings found	factory mark
Typology	single
Type of insulation	partial
Easy insertion input	Yes
Self-extinguishing fire class according to UL 94	V0
Reinforced with anti-vibration collar	No

WEIGHT AND DIMENSIONS

Tip type	blade
----------	-------

CLASSIFICATION AND DATA ORDERING

Electrocode	3681
ETIM Class 7	Solderless copper terminals for copper conductors [EC001052]
Customs code	85369010

MATERIAL COMPOSITION AND TREATMENTS


Conductor body material	Rame elettrolitico con purezza superiore al 99,95%
Minimum thickness of the surface coating of the conducting body	3 μm
Surface treatment of the conductor body	tin plating
Annealing	Yes
Internal surface of the barrel	knurled
Halogen free	No

LOGISTIC

Type of packaging	; box
Unit in minimal packaging	100 PCE
Unit in standard packaging	100 PCE

CERTIFICATIONS

ROHS compliant	Yes
----------------	-----



RF-PP		Insulated cover colour Red RAL 9005	Range of cable cross section 0.25 ÷ 1.5 mm ²									
tipo	Reference standard	Insulated cover material	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Gross weight [g]
RF-PP12	UL 486A-486B; UL 486C	PVC	3	12.8	22.8	4.2	10.1	4	5.5	1.8	4.6	0,700
RF-PP12/1	UL 486A-486B; UL 486C	PVC	3	11.3	21.3	4.2	10.1	4	5.5	1.8	4.6	0,661
RF-PP12/19	UL 486A-486B; UL 486C	PVC	1.9	13.2	23.2	4.2	10.1	4	5.5	1.8	4.6	0,640
RF-PP12/23	UL 486A-486B; UL 486C	PVC	2.3	13.2	23.2	4.2	10.1	4	5.5	1.8	4.6	0,638
RF-PP14	UL 486A-486B; UL 486C	PVC	3	14.8	24.8	4.2	10.1	4	5.5	1.8	4.6	0,744
RF-PP16/23	UL 486A-486B; UL 486C	PVC	2.3	17.2	27.2	4.2	10.1	4	5.5	1.8	4.6	0,680

BF-PP		Insulated cover colour Blue RAL 5015	Range of cable cross section 1.5 ÷ 2.5 mm ²									
tipo	Reference standard	Insulated cover material	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Gross weight [g]
BF-PP10	UL 486A-486B; UL 486C	PVC polyvinylchloride	3.5	10	20	4.2	10.1	4.9	6.4	2.4	4.6	0,750
BF-PP12	UL 486A-486B; UL 486C	PVC polyvinylchloride	3.5	12.8	22.8	4.2	10.1	4.9	6.4	2.4	4.6	0,820
BF-PP12/25	UL 486A-486B; UL 486C	PVC polyvinylchloride	2.5	13.3	23.3	4.2	10.1	4.9	6.4	2.4	4.6	0,750
BF-PP12/29	UL 486A-486B; UL 486C	PVC polyvinylchloride	2.9	13.3	23.3	4.2	10.1	4.9	6.4	2.4	4.6	0,799
BF-PP16/25	UL 486A-486B; UL 486C	PVC polyvinylchloride	2.5	17.2	27.2	4.2	10.1	4.9	6.4	2.4	4.6	0,800

GF-PP	Insulated cover colour Yellow RAL 1021	Range of cable cross section 4 ÷ 6 mm²									
tipo	Insulated cover material	B [mm]	P [mm]	L [mm]	A [mm]	C [mm]	Ø2 [mm]	Ø3 [mm]	Ø [mm]	Cable stripping length [mm]	Gross weight [g]
GF-PP12	PVC polyvinylchloride	4	13.3	27.4	6.4	14.1	6.6	8.1	3.6	7	1,780
GF-PP17	PVC polyvinylchloride	2.9	19.1	33.3	6.4	14.1	6.6	8.1	3.6	7	1,760