

TS 32X15 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Terminal rail, without slot, Accessories, 33 x 15 x 2000 mm, Steel, galvanic zinc plated and passivated
Order No.	0122800000
Type	TS 32X15 2M/ST/ZN
GTIN (EAN)	4008190066307
Qty.	2 m

Creation date 09 July 2024 16:14:42 CEST

Catalogue status 29.06.2024 / We reserve the right to make technical changes.

TS 32X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	15 mm	Depth (inches)	0.591 inch
Height	33 mm	Height (inches)	1.299 inch
Width	2,000 mm	Width (inches)	78.74 inch
Net weight	360 g		

Mounting rail

Installation advice	Direct mounting		
Length of the terminal rail	nominal	2,000 mm	
	max.	2,000 mm	
	min.	0 mm	
Material	Steel		
Pre-punched mounting rail	No		
Short circuit strength corresponds to E-Cu wire	35 mm ²		
Short-time withstand current per second according to IEC 60947-7-2	4.2 kA		
Slit gap			
Slit length			
Slit width			
Standards	DIN EN 60715		
Surface finish	galvanic zinc plated and passivated		
Thickness	1.5 mm		

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ETIM 9.0	EC001285
ECLASS 9.0	27-40-06-02	ECLASS 9.1	27-40-06-02
ECLASS 10.0	27-40-06-02	ECLASS 11.0	27-40-06-02
ECLASS 12.0	27-40-06-02	ECLASS 13.0	27-40-06-02

Environmental Product Compliance

REACH SVHC /

Approvals

ROHS Conform

Downloads

Engineering Data	CAD data – STEP
Engineering Data	Zuken E3.S
User Documentation	Storage Conditions Terminal Blocks
Catalogues	Catalogues in PDF-format
Brochures	

Data sheet

TS 32X15 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

