

TS 20/CX10 2M/ST/ZN**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

General ordering data

Version	Terminal rail, without slot, Accessories, 10 x 10 x 2000 mm, Steel, galvanized
Order No.	0316400000
Type	TS 20/CX10 2M/ST/ZN
GTIN (EAN)	4032248017331
Qty.	2 m

Creation date 09 July 2024 16:20:27 CEST

Catalogue status 29.06.2024 / We reserve the right to make technical changes.

TS 20/CX10 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	10 mm	Depth (inches)	0.394 inch
Height	10 mm	Height (inches)	0.394 inch
Width	2,000 mm	Width (inches)	78.74 inch
Net weight	460 g		

Mounting rail

Installation advice Direct mounting

Length of the terminal rail	nominal	2,000 mm
	max.	2,000 mm
	min.	0 mm

Material Steel

Pre-punched mounting rail No

Slit gap

Slit length

Slit width

Standards DIN EN 60715

Surface finish galvanized

Thickness 1.5 mm

Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ETIM 9.0	EC001285
ECLASS 9.0	27-40-06-02	ECLASS 9.1	27-40-06-02
ECLASS 10.0	27-40-06-02	ECLASS 11.0	27-40-06-02
ECLASS 12.0	27-40-06-02	ECLASS 13.0	27-40-06-02

Environmental Product Compliance

REACH SVHC /

Approvals

ROHS Conform

Downloads

Engineering Data	CAD data – STEP
User Documentation	StorageConditionsTerminalBlocks
Catalogues	Catalogues in PDF-format

Data sheet

TS 20/CX10 2M/ST/ZN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

