

# ARCA 505021 No MP



Sample image

**Order symbol :** ARCA 505021 No MP

**Product nr :** 8120032N

UL Code : UL508A

**Description :** Cabinet, PC

**Remarks :** Grey cover, 2-point locking, hinges on the long side

**EAN :** 6418074314659

**El. number :**

- Finland : 3424591
- Denmark : 8212097609

**Including :** Cabinet base. door with PUR gasket. 3mm double bit lock(s) with key. S versions with swinghandle 2-point locking system. Door guide included.

| <b>Dimensions :</b> | <b>Height</b> | <b>Width</b> | <b>Depth</b> |
|---------------------|---------------|--------------|--------------|
| mm :                | 500           | 500          | 210          |
| inch :              | 19.69         | 19.69        | 8.27         |

#### **Materials :**

|                   |                      |
|-------------------|----------------------|
| Material :        | Polycarbonate        |
| Base colour :     | RAL_7035             |
| Cover colour :    | RAL 7035 -light grey |
| Gasket material : | Polyurethane         |

#### **Temperatures :**

|                               |             |
|-------------------------------|-------------|
| Temperature °C (short term) : | -40 ... 120 |
| Temperature °C (continuous) : | -40 ... 80  |
| Temperature °F (short term) : | -40 ... 250 |
| Temperature °F (continuous) : | -40 ... 175 |

#### **Accessories :**

|                 |  |
|-----------------|--|
| MPMP ARCA 5050  | Mounting plate multiperforated (450x450x2 mm - ø3.6 mm)<br>(450 x 450 x 1) |
| MPX ARCA 5050   | Mounting plate (450x450 mm)<br>(450 x 450 x 15)                            |
| MPS ARCA 5050   | Mounting plate (450x450x2 mm)<br>(450 x 450 x 2)                           |
| DRS ARCA 505021 | DIN rail frame set<br>(480 x 480 x 30)                                     |
| RCS ARCA 5050   | Rain canopy set for size 5050<br>(30 x 500 x 20)                           |
| IDS ARCA 5050   | Inner door set<br>(480 x 480 x 30)   |
| MPP ARCA 5050   | Mounting plate perforated (450x450x2 mm - 26x11 mm)<br>(450 x 450 x 2)     |
| PMK ARCA 50     | PoleMounting kit, for pole ø100-300mm<br>(485 x 385 x 35)                  |

#### **Ratings :**

|   |                   |
|---|-------------------|
| Ingress protection (EN 60529):          | IP66;             |
| Impact Resistance (EN 62262):           | IK10;             |
| electrical_insulation :                 | Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815) : | Yes               |

|                                   |                    |
|-----------------------------------|--------------------|
| UV resistance :                   | UL 746C            |
| Flammability Rating :             | UL 94 5VA          |
| Glow Wire Test (IEC 695-2-1) °C : | 960C               |
| UL Type                           | NEMA__1_4_4X_12_13 |