






## ISOMAX - ISO 5599-1 - Sizes 1, 2 & 3

### Pneumatic remote pilot operated







With direct valve spool manual override

Symbol	Description	Size	Weight (g)	Order code
	5/2 Air pilot - Spring return	1 - 43 mm	350	<b>DX1-421-70</b>
		2 - 56 mm	600	<b>DX2-421-70</b>
		3 - 71 mm	1100	<b>DX3-421-70</b>
	5/2 Air pilot - Differential	1 - 43 mm	350	<b>DX1-451-70</b>
		2 - 56 mm	600	<b>DX2-451-70</b>
		3 - 71 mm	1100	<b>DX3-451-70</b>
	5/2 Double air pilot	1 - 43 mm	350	<b>DX1-406-70</b>
		2 - 56 mm	600	<b>DX2-406-70</b>
		3 - 71 mm	1100	<b>DX3-406-70</b>
	5/3 Closed Center	1 - 43 mm	350	<b>DX1-416-70</b>
		2 - 56 mm	600	<b>DX2-416-70</b>
		3 - 71 mm	1100	<b>DX3-416-70</b>
	5/3 Vented Center	1 - 43 mm	350	<b>DX1-411-70</b>
		2 - 56 mm	600	<b>DX2-411-70</b>
		3 - 71 mm	1100	<b>DX3-411-70</b>
	5/3 Pressurised Center	1 - 43 mm	350	<b>DX1-413-70</b>
		2 - 56 mm	600	<b>DX2-413-70</b>

## ISOMAX - ISO 5599-1 - Sizes 1, 2 & 3

### Pneumatic remote pilot operated

Without direct valve spool manual override

Symbol	Description	Size	Weight (g)	Order code
	5/2 Air pilot - Spring return	1 - 43 mm	350	<b>DX1-421-60</b>
		2 - 56 mm	600	<b>DX2-421-60</b>
		3 - 71 mm	1100	<b>DX3-421-60</b>
	5/2 Air pilot - Differential	1 - 43 mm	350	<b>DX1-451-60</b>
		2 - 56 mm	600	<b>DX2-451-60</b>
		3 - 71 mm	1100	<b>DX3-451-60</b>
	5/2 Double air pilot	1 - 43 mm	350	<b>DX1-406-60</b>
		2 - 56 mm	600	<b>DX2-406-60</b>
		3 - 71 mm	1100	<b>DX3-406-60</b>
	5/3 Closed Center	1 - 43 mm	350	<b>DX1-416-60</b>
		2 - 56 mm	600	<b>DX2-416-60</b>
		3 - 71 mm	1100	<b>DX3-416-60</b>
	5/3 Vented Center	1 - 43 mm	350	<b>DX1-411-60</b>
		2 - 56 mm	600	<b>DX2-411-60</b>
		3 - 71 mm	1100	<b>DX3-411-60</b>
	5/3 Pressurised Center	1 - 43 mm	350	<b>DX1-413-60</b>
		2 - 56 mm	600	<b>DX2-413-60</b>