



## Global ISO Valves for the Rail Industry










### Side ported subbases

Description	Size	Port size	Weight kg	Order code BSP
 <b>Single subbase</b> 1 3 5 2 4 ports & 12 14	1 - 43 mm	G1/4	0.160	<b>PL1-1/4-70</b>
	1 - 43 mm	G3/8	0.160	<b>PL1-3/8-70</b>
	2 - 56 mm	G3/8	0.280	<b>PL2-3/8-70</b>
	2 - 56 mm	G1/2		<b>P2N-HS514SS</b>
	3 - 71 mm	G1/2		<b>PL3-1/2-70</b>
	3 - 71 mm	G3/4		<b>P2N-JS516SD</b>





### Bottom ported subbases

Description	Size	Port size	Weight kg	Order code BSP
 <b>Single subbase</b> 1 3 5 2 4 ports & 12 14	1 - 43 mm	G1/4	0.370	<b>PD1-1/4-70</b>
	2 - 56 mm	G3/8	0.590	<b>PD2-3/8-70</b>
	3 - 71 mm	G1/2	0.590	<b>PD3-1/2-70</b>

### Size 1 bottom ported manifold

Description	Size	Port size	Weight kg	Order code
  <b>Manifold</b> With bottom ports low profile	1 - 43 mm	G1/4	0.200	<b>P2N-AM512MB</b>
  <b>Connecting block</b> Top or bottom ported connecting block for above manifold "low profile"	1 - 43 mm	G3/8	0.150	<b>P2N-AM513GT</b>
  <b>End</b> End piece for above manifold "low profile"	1 - 43 mm	no	0.060	<b>P2N-AM500J</b>
  <b>Intermediate supply</b> Top or bottom ported intermediate supply for above manifold "low profile"	1 - 43 mm	G3/8	0.140	<b>P2N-AM513BT</b>
 <b>Isolation plugs</b> Isolating seal for above manifold "low profile"	1 - 43 mm		0.070	<b>P2N-AK0P</b>

### Sizes 1 & 2 side ported manifold

Description	Size	Port size	Weight kg	Order code
  <b>Manifold</b> Manifold with side ports	1 - 43 mm	G1/4	0.240	<b>P2N-EM512MD</b>
	2 - 56 mm	G3/8	0.210	<b>P2N-FM513MD</b>
  <b>End</b> Side ported connecting kit for above manifold with side ports	1 - 43 mm	G3/8	0.360	<b>P2N-EM513ES</b>
	2 - 56 mm	G1/2	0.290	<b>P2N-FM514ES</b>

 Indicates stocked products.