

9000.10

SPLIT CABLE ENTRY SYSTEMS FOR PREDETERMINED CABLES, MADE IN GLASS-FIBRE REINFORCED POLYAMIDE PA6.6 WITH OVERMOULDED SEAL



CERTIFICATIONS & APPROVALS

 UL (cURus)

Features

TECHNICAL INFORMATION

| | |
|--|----------------|
| Range of operating temperature (static) | -40 ÷ 140 °C |
| Ingress Protection | IP66 |
| External seal | No |
| Colour | Black RAL 9005 |
| Self-extinguishing fire class according to UL 94 | V0 |
| Presence of overmolded gasket | Yes |

WEIGHT AND DIMENSIONS

| | |
|---|---------|
| Fixing hole diameter | 5.5 mm |
| Height | 61 mm |
| Length | 99.5 mm |
| Vertical centre distance between the fixing holes | 32 mm |
| Horizontal centre distance between the fixing holes | 83 mm |
| Depth | 19.5 mm |

CLASSIFICATION AND DATA ORDERING

| | |
|--------------|---|
| ETIM Class | Gland plate for small distribution boards/switchgear cabinets 7 [EC000211] |
| Customs code | 39269097 |

MATERIAL COMPOSITION AND TREATMENTS

| | |
|----------------------------|----------------------------------|
| Material | Polyamide PA6.6 + Glass fiber FB |
| Silicone-free | Yes |
| Halogen free | Yes |
| Overmolded gasket material | TPE elastomer |

LOGISTIC

| | |
|---------------------|------------|
| Storage temperature | 10 ÷ 25 °C |
| Type of packaging | box |

CERTIFICATIONS

| | |
|----------------|-----|
| UL standard | 50E |
| ROHS compliant | Yes |
| EN ISO 4892-2 | Yes |

9000.10

| tipo | Number of small grommets | Number of large grommets | Gross weight [g] |
|-----------|--------------------------|--------------------------|------------------|
| 9000.10/3 | 2 | 1 | 105,270 |
| 9000.10/6 | 6 | 0 | 108,270 |