

## 9000.Q

SPLIT CABLE ENTRY SYSTEMS FOR PREDETERMINED CABLES, MADE IN GLASS-FIBRE REINFORCED POLYAMIDE PA6.6 WITH OVERMOULDED SEAL



### CERTIFICATIONS & APPROVALS

 UL (cURus)

## Features

### TECHNICAL INFORMATION

Range of operating temperature (static)	-40 ÷ 140 °C
Ingress Protection	IP66
External seal	No
Colour	Black RAL 9005
Self-extinguishing fire class according to UL 94	V0
Presence of overmolded gasket	Yes

### MATERIAL COMPOSITION AND TREATMENTS

Material	Polyamide PA6.6 + Glass fiber FB
Silicone-free	Yes
Halogen free	Yes
Overmolded gasket material	TPE elastomer

### WEIGHT AND DIMENSIONS

Fixing hole diameter	5.5 mm
Height	61 mm
Length	75 mm
Vertical centre distance between the fixing holes	32 mm
Horizontal centre distance between the fixing holes	58 mm
Depth	19.5 mm

### LOGISTIC

Storage temperature	10 ÷ 25 °C
Type of packaging	box

### CLASSIFICATION AND DATA ORDERING

ETIM Class	Gland plate for small distribution boards/switchgear cabinets 7 [EC000211]
Customs code	39269097

### CERTIFICATIONS

UL standard	50E
ROHS compliant	Yes
EN ISO 4892-2	Yes

## 9000.Q

tipo	Number of small grommets	Number of large grommets	Gross weight [g]
9000.Q/1	0	1	89,500
9000.Q/4	4	0	87,500