

9000.R

SPLIT CABLE ENTRY SYSTEMS FOR PREDETERMINED CABLES, MADE IN GLASS-FIBRE REINFORCED POLYAMIDE PA6.6 WITH OVERMOULDED SEAL



CERTIFICATIONS & APPROVALS

 UL (cURus)

Features

TECHNICAL INFORMATION

Range of operating temperature (static)	-40 ÷ 140 °C
Ingress Protection	IP66
External seal	No
Colour	Black RAL 9005
Self-extinguishing fire class according to UL 94	V0
Presence of overmolded gasket	Yes
Number of large grommets	0

WEIGHT AND DIMENSIONS

Fixing hole diameter	5.5 mm
Height	42 mm
Vertical centre distance between the fixing holes	0 mm
Depth	19.5 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class	Gland plate for small distribution boards/switchgear cabinets
7	[EC000211]
Customs code	39269097

MATERIAL COMPOSITION AND TREATMENTS

Material	Polyamide PA6.6 + Glass fiber FB
Silicone-free	Yes
Halogen free	Yes
Overmolded gasket material	TPE elastomer

LOGISTIC

Storage temperature	10 ÷ 25 °C
Type of packaging	box

CERTIFICATIONS

UL standard	50E
ROHS compliant	Yes
EN ISO 4892-2	Yes

9000.R

tipo	Number of small grommets	L [mm]	Horizontal centre distance between the fixing holes [mm]	Gross weight [g]
9000.R/2	2	75	58	67,500
9000.R/3	3	99.5	83	81,500
9000.R/4	4	120	103	92,670
9000.R/5	5	147	130	120,270