



## E2E-X14B1T18-M1

Proximity sensor, inductive, nickel-brass, short body, M18, shielded, 14 mm, DC, 3-wire, PNP NO, IO-Link COM3, M12 connector

# Specifications

Size	M18
Mounting type	Quasi-flush
Sensing distance	14 mm
Overall length of sensor	53 mm
Thread length	33 mm
Material housing	Brass, nickel plated
Output type	IO-Link, PNP
Operation mode	NO
Connection method	Connector M12
Cable specifications	-
IO-Link function	✓
IO-Link baud rate	COM3 (230.4 kbps)
Degree of protection (IP)	IP67/IP69K

# Accessories



Y92E-J18S30

Mounting Sleeves e-jig for M18 Prox

# Related products



## M12 Connectors & Cordsets

Industrial connectors & cordsets for any application

# Downloads

CAD Library



### E2E NEXT Datasheet

EN PDF 38.9 MB



### E2E(Q) - Basic Models Index list

EN PDF 719 KB



### E2E(Q) - Premium Models Index list

EN PDF 719 KB



### E2E[Q]-XxBxxxx IO-Link IODD file

EN ZIP 1.35 MB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 7.5 MB

# Environmental product information

Part number	RoHS (EU)2015/863	REACH	SVHC contained
E2E-X14B1T18-M1TJ 0.3M	?	?	?



*Dispose in accordance with applicable regulations.*

*SVHC content information has been adapted as a result of the adoption at our company of chemSHERPA v.2, the Japanese standard for chemical information sharing and exchange throughout the supply chain.*

*We continuously make our best effort to communicate compliance information transparently to our customers, however some information may still be in the process to be collected or displayed. So don't hesitate to contact us in case a specific product or information you're looking for can't be found here.*

## TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 21 November, 2024. Click here for [terms of use](#).

**OMRON**

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU