



## D4NS-1BF

Safety-door switch, Plastic, Tongue operated, PG13.5 (1-conduit), 2NC (slow-action)

# Specifications

Door switch type	Key-operated
Guard-lock	×
Material housing	Resin
Material head	Resin
Ambient temperature (operating)	-30-70 °C
Direction of operation	Adjustable
Door contacts NC	2
Door contacts NO	0
Switch action	Slow action
Make before break	×
LED indicator	×
Connection method	Terminal block
Cable length	0 m
Degree of protection (IP)	IP67
Conduit size	PG13.5
Number of conduits	1
Shape	Cuboid
Overall length of sensor	96 mm
Height of sensor	30 mm
Width of sensor	31 mm

# Accessories



**D4DS-K1**

Operation key for D4NL/NS; horizontal mounting



**D4DS-K2**

Operation key for D4NL/NS; vertical mounting



**D4DS-K3**

Operation key for D4NL/NS; adjustable mounting (horizontal)



**D4DS-K5**

Operation key for D4NL/NS; adjustable mounting (horizontal/vertical)

# Downloads

CAD Library



**D4NS Safety-door Switch**

**Datasheet**

**EN** PDF 642 KB



**D4NS/D4NS-SK Safety-door Switch**

**Datasheet**

**EN** PDF 3.82 MB



**EAC Mark removal Discontinuation Notice**

**EN** PDF 221 KB



**Machine Safety Catalogue**

**EN** PDF 9.91 MB



**Machine Safety Solution Brochure**

**EN** PDF 2.86 MB



**Safety Component Selection Guide EU**

**Brochure**

**EN** PDF 5.26 MB



**Safety Interlock Switches**

**Brochure**

**EN** PDF 1.52 MB



**Safety Solution Advanced Guide**

**Guide**

**EN** PDF 2.57 MB



**Safety Solution Basic Guide**

**Guide**

**EN** PDF 14.4 MB

