



## E2E-X4C112 5M

Proximity sensor, inductive, nickel-brass, short body, M12, shielded, 4 mm, DC, 3-wire, NPN NO, 5 m cable

# Specifications

|                           |                      |
|---------------------------|----------------------|
| Size                      | M12                  |
| Mounting type             | Quasi-flush          |
| Sensing distance          | 4 mm                 |
| Overall length of sensor  | 47.1 mm              |
| Thread length             | 29 mm                |
| Material housing          | Brass, nickel plated |
| Output type               | NPN                  |
| Operation mode            | NO                   |
| Connection method         | Cable                |
| Cable specifications      | PVC (oil-resistant)  |
| Cable length              | 5 m                  |
| IO-Link function          | ×                    |
| IO-Link baud rate         | Not Applicable       |
| Degree of protection (IP) | IP67/IP67G/IP69K     |

# Accessories



Y92E-J12S18

Mounting Sleeves e-jig for M12 Prox

## CAD Library



### E2E NEXT Datasheet

EN PDF 38.9 MB



### E2E(Q) - Basic Models Index list

EN PDF 719 KB



### E2E(Q) - Premium Models Index list

EN PDF 719 KB



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB



### IO-Link Series Brochure

EN PDF 7.5 MB