

Eaton 276883

Catalog Number: 276883

Eaton Moeller® series DILM Contactor, 3 pole, 380 V 400 V 5.5 kW, 1 NC, 110 V DC, DC operation, Screw terminals

General specifications



Photo is representative

Product Name	Catalog Number
Eaton Moeller® series DILM contactor	276883

Model Code	EAN
DILM12-01(110VDC)	4015082768836

Product Length/Depth	Product Height
75 mm	68 mm

Product Width	Product Weight
45 mm	0.296 kg

Certifications	Catalog Notes
VDE 0660	Contacts according to EN 50012

UL File No.: E29096

IEC/EN 60947-4-1

IEC/EN 60947

UL

CSA Class No.: 2411-03, 3211-04

CSA

CE

CSA File No.: 012528

UL Category Control No.: NLDX

UL 508

CSA-C22.2 No. 14-05

Features & Functions

Fitted with:

Varistor suppressor circuit

Mirror contact

Number Of Poles

Three-pole

General

Application

Contactors for Motors

Frame size

FS1

Lifespan, mechanical

10,000,000 Operations (DC operated)

Operating frequency

9000 mechanical Operations/h (DC operated)

Overvoltage category

III

Pollution degree

3

Product category

Contactors

Protection

Finger and back-of-hand proof, Protection against direct contact when actuated from front (EN 50274)

Rated impulse withstand voltage (Uimp)

8000 V AC

Resistance per pole

4.6 m Ω

Suitable for

Also motors with efficiency class IE3

Utilization category

AC-1: Non-inductive or slightly inductive loads, resistance furnaces

AC-3: Normal AC induction motors: starting, switch off during running

AC-4: Normal AC induction motors: starting, plugging, reversing, inching

Voltage type

DC

Ambient conditions, mechanical

Shock resistance

7 g, N/O auxiliary contact, Mechanical, according to IEC/EN

Climatic environmental conditions

Ambient operating temperature - min

-25 °C

60068-2-27, Half-sinusoidal shock 10 ms
5 g, N/C auxiliary contact, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 10 ms
5.7 g, N/O main contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms
3.4 g, N/O auxiliary contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms
3.4 g, N/C auxiliary contact, Mechanical, according to IEC/EN
60068-2-27 when tabletop-mounted, Half-sinusoidal shock 10
ms
10 g, N/O main contact, Mechanical, according to IEC/EN
60068-2-27, Half-sinusoidal shock 10 ms

Ambient operating temperature - max

60 °C

Ambient operating temperature (enclosed) - min

-25 °C

Ambient operating temperature (enclosed) - max

40 °C

Ambient storage temperature - min

-40 °C

Ambient storage temperature - max

80 °C

Climatic proofing

Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30

Electro Magnetic Compatibility

Emitted interference

According to EN 60947-1

Interference immunity

According to EN 60947-1

Terminal capacities

Terminal capacity (flexible with ferrule)

1 x (0.75 - 2.5) mm²

2 x (0.75 - 2,5) mm²

Terminal capacity (solid)

2 x (0.75 - 2.5) mm²

1 x (0.75 - 4) mm²

Terminal capacity (solid/stranded AWG)

Single 18 - 10, double 18 - 14

Stripping length (main cable)

10 mm

Stripping length (control circuit cable)

10 mm

Screw size

M3.5, Terminal screw

Screwdriver size

0.8 x 5.5/1 x 6 mm, Terminal screw, Standard screwdriver

2, Terminal screw, Pozidriv screwdriver

Tightening torque

1.2 Nm, Screw terminals

Electrical Rating

Short-circuit rating

Rated breaking capacity at 220/230 V

120 A

Rated breaking capacity at 380/400 V

120 A

Rated breaking capacity at 500 V

100 A

Rated breaking capacity at 660/690 V

70 A

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V

22 A

Rated operational current (I_e) at AC-3, 220 V, 230 V, 240 V

12 A

Rated operational current (I_e) at AC-3, 380 V, 400 V, 415 V

12 A

Rated operational current (I_e) at AC-3, 440 V

12 A

Rated operational current (I_e) at AC-3, 500 V

10 A

Rated operational current (I_e) at AC-3, 660 V, 690 V

7 A

Rated operational current (I_e) at AC-4, 220 V, 230 V, 240 V

7 A

Rated operational current (I_e) at AC-4, 400 V

7 A

Rated operational current (I_e) at AC-4, 500 V

6 A

Rated operational current (I_e) at AC-4, 660 V, 690 V

5 A

Rated operational current (I_e) at DC-1, 60 V

20 A

Rated operational current (I_e) at DC-1, 110 V

20 A

Rated operational current (I_e) at DC-1, 220 V

15 A

Rated insulation voltage (U_i)

690 V

Rated operational current (I_e) at AC-1, 380 V, 400 V, 415 V

Short-circuit current rating (basic rating)

60 A, max. CB, SCCR (UL/CSA)

45 A, max. Fuse, SCCR (UL/CSA)

5 kA, SCCR (UL/CSA)

Short-circuit current rating (high fault at 480 V)

30/100 kA, Fuse, SCCR (UL/CSA)

25 A, Class RK5/ 45 A Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit current rating (high fault at 600 V)

30/100 kA, Fuse, SCCR (UL/CSA)

25 A, Class RK5/45 A, Class J, max. Fuse, SCCR (UL/CSA)

Short-circuit protection rating (type 1 coordination) at 400 V

35 A gG/gL

Short-circuit protection rating (type 1 coordination) at 690 V

25 A gG/gL

Short-circuit protection rating (type 2 coordination) at 400 V

20 A gG/gL

Short-circuit protection rating (type 2 coordination) at 690 V

20 A gG/gL

Conventional thermal current

Conventional thermal current I_{th} (1-pole, enclosed)

45 A

Conventional thermal current I_{th} (3-pole, enclosed)

18 A

Conventional thermal current I_{th} at 55°C (3-pole, open)

21 A

Conventional thermal current I_{th} of main contacts (1-pole, open)

50 A

Switching capacity

Switching capacity (main contacts, general use)

20 A, Maximum motor rating (UL/CSA)

Switching capacity (auxiliary contacts, general use)

1 A, 250 V DC, (UL/CSA)

10 A, 600 V AC, (UL/CSA)

Switching capacity (auxiliary contacts, pilot duty)

A600, AC operated (UL/CSA)

22 A

Rated operational power at AC-3, 240 V, 50 Hz

4 kW

Rated operational power at AC-3, 380/400 V, 50 Hz

5.5 kW

Rated operational power at AC-3, 415 V, 50 Hz

7 kW

Rated operational power at AC-4, 220/230 V, 50 Hz

2 kW

Rated operational power at AC-4, 240 V, 50 Hz

2.2 kW

Rated operational power at AC-4, 415 V, 50 Hz

3.4 kW

Rated operational power at AC-4, 440 V, 50 Hz

3.6 kW

Rated operational power at AC-4, 500 V, 50 Hz

3.5 kW

Rated operational power at AC-4, 660/690 V, 50 Hz

4.4 kW

Rated operational voltage (U_e) at AC - max

690 V

P300, DC operated (UL/CSA)

Switching time

Arcing time

10 ms

Switching time (DC operated, make contacts, closing delay) - max

31 ms

Switching time (DC operated, make contacts, opening delay) - max

12 ms

Magnet system

Drop-out voltage

0.6 - 0.15 x U_C, DC operated

At least smoothed two-phase bridge rectifier or three-phase rectifier

Duty factor

100 %

Pick-up voltage

0.8 - 1.1 V DC x U_C

0.85 - 1.1 V DC x U_C (only with auxiliary contact module with 3 or more N/C contacts)

Power consumption (pick-up) at DC

4.5 W

Power consumption (sealing) at DC

4.5 W

Rated control supply voltage (U_s) at AC, 50 Hz - min

0 V

Rated control supply voltage (U_s) at AC, 50 Hz - max

0 V

Rated control supply voltage (U_s) at AC, 60 Hz - min

0 V

Rated control supply voltage (U_s) at AC, 60 Hz - max

0 V

Rated control supply voltage (U_s) at DC - min

110 V

Rated control supply voltage (U_s) at DC - max

110 V

Motor Rating

Assigned motor power at 115/120 V, 60 Hz, 1-phase
1 HP

Assigned motor power at 200/208 V, 60 Hz, 3-phase
3 HP

Assigned motor power at 230/240 V, 60 Hz, 1-phase
2 HP

Assigned motor power at 230/240 V, 60 Hz, 3-phase
3 HP

Assigned motor power at 460/480 V, 60 Hz, 3-phase
10 HP

Assigned motor power at 575/600 V, 60 Hz, 3-phase
10 HP

Communication

Connection to SmartWire-DT

No

Contacts

Number of contacts (normally closed contacts)

1

Number of contacts (normally open contacts)

0

Number of auxiliary contacts (normally closed contacts)

1

Number of auxiliary contacts (normally open contacts)

0

Safety

Safe isolation

400 V AC, Between the contacts, According to EN 61140

400 V AC, Between coil and contacts, According to EN 61140

Special purpose ratings

Special purpose rating of ballast electrical discharge lamps

20 A (480V 60Hz 3phase, 277V 60Hz 1phase)

20 A (600V 60Hz 3phase, 347V 60Hz 1phase)

Special purpose rating of definite purpose rating

12 A, FLA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)

72 A, LRA 480 V 60 Hz 3-ph, 100,000 cycles acc. to UL 1995,
(UL/CSA)

Special purpose rating of elevator control

2 HP, 200 V 60 Hz 3-ph, (UL/CSA)

7.8 A, 200 V 60 Hz 3-ph, (UL/CSA)

2 HP, 240 V 60 Hz 3-ph, (UL/CSA)
7.5 HP, 600 V 60 Hz 3-ph, (UL/CSA)
7.5 HP, 480 V 60 Hz 3-ph, (UL/CSA)
11 A, 480 V 60 Hz 3-ph, (UL/CSA)
6.8 A, 240 V 60 Hz 3-ph, (UL/CSA)
9 A, 600 V 60 Hz 3-ph, (UL/CSA)

Special purpose rating of refrigeration control (CSA only)

60 A, LRA 480 V 60 Hz 3phase; (CSA)
10 A, FLA 480 V 60 Hz 3phase; (CSA)
60 A, LRA 600 V 60 Hz 3phase; (CSA)
10 A, FLA 600 V 60 Hz 3phase; (CSA)

Special purpose rating of resistance air heating

20 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)
20 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)

Special purpose rating of tungsten incandescent lamps

14 A, 480 V 60 Hz 3phase, 277 V 60 Hz 1phase, (UL/CSA)
14 A, 600 V 60 Hz 3phase, 347 V 60 Hz 1phase, (UL/CSA)

Design verification

Equipment heat dissipation, current-dependent P_{vid}

1.5 W

Heat dissipation capacity P_{diss}

0 W

Rated operational current for specified heat dissipation (I_n)

12 A

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.2.7 Inscriptions

Meets the product standard's requirements.

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

10.8 Connections for external conductors

Is the panel builder's responsibility.

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Resources

Catalogues

[Switching and protecting motors - catalog](#)

[SmartWire-DT Catalog](#)

[eaton-product-overview-for-machinery-catalogue-ca08103003zen-en-us.pdf](#)

[Product Range Catalog Switching and protecting motors](#)

Certification reports

[0000SPC-571](#)

Characteristic curve

[2100DIA-8](#)

[eaton-contactors-switch-dilm-characteristic-curve.eps](#)

[210U039](#)

[210U038](#)

[eaton-contactors-switch-dilm-characteristic-curve-002.eps](#)

[eaton-contactors-component-dilm-characteristic-curve-003.eps](#)

[eaton-contactors-short-time-loading-dilm-characteristic-curve.eps](#)

[2100DIA-7](#)

Declarations of conformity

[DA-DC-00004810.pdf](#)

[DA-DC-00004792.pdf](#)

Drawings

[210N018](#)

[210T013](#)

[eaton-contactors-module-dilm-dimensions-002.eps](#)

[eaton-contactors-mounting-dilm-dimensions-002.eps](#)

[eaton-contactors-mounting-dilm-dimensions.eps](#)

[eaton-contactors-module-dilm-dimensions.eps](#)

[2110DIM-1](#)

[2110DIM-2](#)

[eaton-contactors-frame-dilm-dimensions.eps](#)

[210N017](#)

Drawings

[eaton-general-ie-ready-dilm-contactor-standards.eps](#)

[210I044](#)

[eaton-contactors-dilm-3d-drawing-007.eps](#)

eCAD model

DA-CE-ETN.DILM12-01(110VDC)

ETN.276883.edz

Installation instructions

eaton-contactors-dila-dilm7-15-dilmp20-instruction-leaflet-il03407013z.pdf

Installation videos

WIN-WIN with push-in technology

mCAD model

DA-CS-dil_m7_15

eaton-cadenas-side_view-dil_m7_15_side.pra

eaton-cadenas-drill_view-dil_m7_15_drill.pra

eaton-cadenas-path-01-geo-dil_m7_15.3db

DA-CD-dil_m7_15

eaton-cadenas-front_view-dil_m7_15_front.pra

System overview

210O154

eaton-contactors-dilm-contactor-system-overview.eps

Wiring diagrams

210S027

2100SWI-126



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia