






3/2 N.C. CNOMO Operator - Without Coil

Description		Manual override	W (g)	Order code
	Solenoid operator for 30 x 30 DIN Form A Coil Dedicated to Low Power 2,5W / 3VA Coil	No manual override	65	P2FP23N4A
		Pulse non locking	65	P2FP23N4B
		Locking	65	P2FP23N4C
	Solenoid operator for 30 x 30 DIN Form A Coil Dedicated to High Power 4,5W / 5VA Coil	No manual override	65	EV3000100
		Pulse non locking	65	EV3001100
		Locking	65	EV3003100
	Solenoid operator for 22 x 30 DIN Form B Coil Dedicated to Low Power 2,5W / 4,5VA Coil	No manual override	65	1EV0*310
		Pulse non locking	65	1EV1*310
		Locking	65	1EV3*310



30 x 30 DIN Form A and 22 x 30 DIN Form B Coils for CNOMO Operator

	Voltage	30 x 30 DIN Form A			22 x 30 DIN Form B	
		W (g)	Order code	Order code	W (g)	Order code
	12 Vdc	105	P2FCA445	P2FCA545	93	P2FCB345
	24 Vdc	105	P2FCA449	P2FCA549	93	P2FCB349
	48 Vdc	105	P2FCA453	P2FCA551	93	P2FCB351
	12 Vac 50/60 Hz	105	P2FCA440	P2FCA540	93	P2FCB340
	24 Vac 50/60 Hz	105	P2FCA445	P2FCA545	93	P2FCB345
	48 Vac 50/60 Hz	105	P2FCA449	P2FCA549	93	P2FCB349
	110 Vac 50 Hz / 120 Vac 60 Hz	105	P2FCA453	P2FCA553	93	P2FCB353
	230 Vac 50 Hz / 240 Vac 60 Hz	105	P2FCA457	P2FCA557	93	P2FCB357



Spare Solenoid Nuts

Description	Usage	W (g)	Order code
 Plastic knurled nut	For valve requiring Captured exhaust	5	P2FNPA
Diffuser plastic nut	For valve requiring Vented exhaust	5	P2FNDA

30 x 30 DIN Form A and 22 x 30 DIN Form B Solenoid Connectors

Description	Characteristic	Visualisation	Cable length	W (g)	Order code	
	30 x 30 DIN Form A connector With standard screw	Standard IP65	No LED	No cable	15	3EV290V10
			24 Vdc/Vac LED	No cable	30	3EV290V20-24
				5 meters	355	3EV290V20-24L5
			110 Vac LED	No cable	30	3EV290V20-110
				5 meters	470	3EV290V20-110L5
			230 Vac LED	No cable	30	3EV290V20-230
5 meters	350	3EV290V20-230L5				
	22 x 30 DIN Form B connector With standard screw	Standard IP65	No LED	No cable	15	3EV10V10
			24 Vdc/Vac LED	No cable	20	3EV10V20-24
				5 meters	350	3EV10V20-24L5
			110 Vac LED	No cable	25	3EV10V20-110
				5 meters	355	3EV10V20-110L5
			230 Vac LED	No cable	25	3EV10V20-230
5 meters	360	3EV10V20-230L5				

M12 Adaptor for 30 x 30 DIN Form A Coil

Description	Characteristics	Visualisation	Cable	W (g)	Order code
 M12 Connector for one coil	24 V AC/DC - 4A	LED	No cable	30	P8C-A626C
 M12 Connector for two coils*	24 V AC/DC - 4A	LED	No cable	70	P8C-AM26C

* : Not compatible with Size 3 Valves (DX3)

Note: Solenoid pilot operators are fitted to the ISO valve range. Order the above part numbers for spares.

The operators are supplied with mounting screws and interface 'O' rings.

Coils and connectors must be ordered separately.