

V series valve island: Communication node for IO-Link

Communication node for 19 outputs (Moduflex Pilot Valves)
 (The last 5 outputs of this 24 DO node can't be used with Moduflex Valve)



Description	IO-Link Class	M12 A coded Connector connection			Weight (g)	Order code
		IO-Link	Aux. Power	Aux. Power Pinout		
P2M IO-Link Communication Node	Class A	3 Pin's	3 Pin's	1 & 3	160	P2M2HBVL12400A13
		3 Pin's	3 Pin's	4 & 3	160	P2M2HBVL12400A43
		3 Pin's	5 Pin's	4 & 2	160	P2M2HBVL12400A42
	Class B	5 Pin's		2 & 5	140	P2M2HBVL12400B25
P2M IO-Link Communication Node Safe Power Capable	Class A	3 Pin's	3 Pin's	1 & 3	165	P2M2HBVL12400A13-SPC
		3 Pin's	3 Pin's	4 & 3	165	P2M2HBVL12400A43-SPC
		3 Pin's	5 Pin's	4 & 2	165	P2M2HBVL12400A42-SPC
	Class B	5 Pin's		2 & 5	145	P2M2HBVL12400B25-SPC

IODD file can be downloaded from IODD Finder or the Moduflex web site:
<https://ioddfinder.io-link.com>
www.parker.com/pde/io-link

Accessories



Description	Connector type	Weight (g)	Order code
Quick connect straight connector for both IO-Link communication and auxiliary power supply	M12 - 5 Pin's Female - A Coding	25	P8CS1205AA