



NB3Q-TW00B-V1

Touch screen HMI, 3.5 inch QVGA (320 x 240 pixel), TFT color

Specifications

Screen diagonal	3.5 in
Number of pixels, horizontal	320
Number of pixels, vertical	240
Type of display	TFT
Frame color	Black
Number of Ethernet ports	0
Number of USB ports	2
Number of RS-232 ports	1
Number of RS-422 ports	1
Number of RS-485 ports	1
Number of colors of the display	65536
Number of grey-scales/blue-scales of display	64
Degree of protection (IP), front side	IP65
Width of the front	129.8 mm
Height of the front	103.8 mm
Width of panel cutout	119 mm
Height of panel cutout	93 mm
Built-in depth	52.8 mm
Product Weight (unpacked)	320 g

Accessories



NB3Q-KBA04

Accessory HMI, protective sheets for NB3Q (5 sheets)



XW2Z-200T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 2 m



XW2Z-500T

Cable, RS-232C, for connecting NT HMI 9-pin port to PLC 9-pin port, 5 m

Downloads

CAD Library



**EAC Mark removal
Discontinuation Notice**

EN PDF 221 KB



**Maxell CR-series button
cells
Battery Safety Datasheet**

EN PDF 132 KB



**NB Faceplate 4.0 -
Multilanguage
Software**

EN ZIP 89.1 MB



**NB Series
Programmable Terminal
Brochure**

EN PDF 4.06 MB



**NB-Designer Setup
v1.5.3.1
Software**

EN ZIP 374 MB



**NB-Designer Setup
v1.6.4.0
Software**

EN ZIP 430 MB



**NB-Series
Getting Started Guide**

EN PDF 10 MB



**NB-Series
Setup Manual**

EN PDF 6.08 MB



**NB-Series Host
Connection
Setup Manual**

EN PDF 21.3 MB

TERMS OF WEBSITE USE

This PDF document was created from the European OMRON Industrial Automation website on 2 July, 2025. Click here for [terms of use](#).

OMRON

INDUSTRIAL AUTOMATION | INDUSTRIAL.OMRON.EU