



## E32-T11N 2M

Fiber optic sensor head, through-beam, M4 hexagonal back, right-angled head, R1 flexible fiber, 2 m cable

# Specifications

|                             |  |
|-----------------------------|--|
| Sensing method              | Through-beam                                   |
| Shape                       | Threaded                                       |
| Size                        | M4   |
| Application                 | Object detection                               |
| Features                    | 90° cable exit, Flexible fiber, Hexagonal back |
| Temperature range           | -40-70 °C                                      |
| Sensing distance            | 3000 mm  |
| Cable length                | 2 m  |
| Bending radius              | 1 mm   |
| Free cut                    | ✓  |
| Material core               | Plastic  |
| Degree of protection (IP)   | IP67   |
| Sensing surface orientation | Right-angle                                    |
| Material sheath             | PVC  |

# Accessories



**E39-F1**

Long-distance lens unit for E32 through-beam fibers with M2.6 thread

## Related products



**E3X-ZV and E3X-MZV**  
Smart Fiber Amplifier



**E3NX-CA**  
High-performance color  
mark sensor



**E3NX-CA**  
High-performance color  
mark sensor



**E3NX-MA**  
Smart Fiber Amplifier Units



**E3NX-FA**  
High-performance digital  
fiber amplifier



**E3X-NA**  
Digital fiber amplifier with  
potentiometer adjustment

## Downloads

CAD Library



**EAC Mark removal  
Discontinuation Notice**

EN PDF 221 KB



**Fiber Sensor Selection  
Selection Guide**

EN PDF 16.2 MB

