

Specifications

Servo control method	EtherCAT
Drive supply voltage	230 V single phase, 230 V three phase
Rated output	0.1 kW
Safety functions	SLS, SS1, STO
Product Height (unpacked)	223 mm
Product Width (unpacked)	40 mm
Product Depth (unpacked)	196.05 mm
Product Weight (unpacked)	1200 g

Fits to



R88M-1M05030T-BS2

1S AC servo motor, 50 W, 230 VAC, 3000 rpm, 0.159 Nm, absolute encoder, with brake



R88M-1M05030T-S2

1S AC servo motor, 50 W, 230 VAC, 3000 rpm, 0.159 Nm, absolute encoder



R88M-1M10030T-BS2

1S AC servo motor, 100 W, 230 VAC, 3000 rpm, 0.318 Nm, absolute encoder, with brake



R88M-1M10030T-S2

1S AC servo motor, 100 W, 230 VAC, 3000 rpm, 0.318 Nm, absolute encoder

CAD Library



1S series with SS1/SLS Safety Sub-Functions Brochure

EN PDF 1.81 MB



1S-series servos with SS1/SLS safety functions Users Manual

EN PDF 28 MB



R88D-1SN_-ECT-51 Instruction Sheet

EN PDF 325 KB



R88M-1__R88D-1SN_-ECT-51 AC Servo Drives 1S-series

Datasheet

EN PDF 9.42 MB