



## R88D-1SN06F-ECT-51

1S-51 servo drive with STO, SS1 and SLS safety, EtherCAT type, 600 W, 3~ 400 VAC

# Specifications

Servo control method	EtherCAT
Drive supply voltage	400 V three phase
Rated output	0.6 kW
Safety functions	SLS, SS1, STO
Product Height (unpacked)	246.4 mm
Product Width (unpacked)	90 mm
Product Depth (unpacked)	236.05 mm
Product Weight (unpacked)	3400 g

## Fits to



### **R88M-1M40020C-BS2**

1S AC servo motor, 400 W, 400 VAC, 2000 rpm, 1.91 Nm, absolute encoder, with brake



### **R88M-1M40020C-S2**

1S AC servo motor, 400 W, 400 VAC, 2000 rpm, 1.91 Nm, absolute encoder



### **R88M-1M60020C-BS2**

1S AC servo motor, 600 W, 400 VAC, 2000 rpm, 2.86 Nm, absolute encoder, with brake



### **R88M-1M60020C-S2**

1S AC servo motor, 600 W, 400 VAC, 2000 rpm, 2.86 Nm, absolute encoder

## CAD Library



### 1S series with SS1/SLS Safety Sub-Functions Brochure

EN PDF 1.81 MB



### 1S-series servos with SS1/SLS safety functions Users Manual

EN PDF 28 MB



### R88D-1SN\_-ECT-51 Instruction Sheet

EN PDF 325 KB



### R88M-1\_R88D-1SN\_-ECT-51 AC Servo Drives 1S-series

#### Datasheet

EN PDF 9.42 MB