



R88D-1SN15H-ECT-51

1S-51 servo drive with STO, SS1 and SLS safety, EtherCAT type, 1.5 kW, 1 or 3~ 230 VAC

Specifications

| | |
|---------------------------|---------------------------------------|
| Servo control method | EtherCAT |
| Drive supply voltage | 230 V single phase, 230 V three phase |
| Rated output | 1.5 kW |
| Safety functions | SLS, SS1, STO |
| Product Height (unpacked) | 246.4 mm |
| Product Width (unpacked) | 90 mm |
| Product Depth (unpacked) | 236.05 mm |
| Product Weight (unpacked) | 3400 g |

Fits to



R88M-1L1K530T-BS2

1S AC servo motor, 1.5 kW, 230 VAC, 3000 rpm, 4.77 Nm, absolute encoder, with brake



R88M-1L1K530T-S2

1S AC servo motor, 1.5 kW, 230 VAC, 3000 rpm, 4.77 Nm, absolute encoder



R88M-1M1K520T-BS2

1S AC servo motor, 1.5 kW, 230 VAC, 2000 rpm, 7.16 Nm, absolute encoder, with brake



R88M-1M1K520T-S2

1S AC servo motor, 1.5 kW, 230 VAC, 2000 rpm, 7.16 Nm, absolute encoder

CAD Library



1S series with SS1/SLS Safety Sub-Functions Brochure

EN PDF 1.81 MB



1S-series servos with SS1/SLS safety functions Users Manual

EN PDF 28 MB



R88D-1SN_-ECT-51 Instruction Sheet

EN PDF 325 KB



R88M-1_R88D-1SN_-ECT-51 AC Servo Drives 1S-series

Datasheet

EN PDF 9.42 MB