



R88D-1SN150F-ECT-51

1S-51 servo drive with STO, SS1 and SLS safety, EtherCAT type, 15 kW, 3-400 VAC

Specifications

Servo control method	EtherCAT
Drive supply voltage	400 V three phase
Rated output	15 kW
Safety functions	SLS, SS1, STO
Product Height (unpacked)	570 mm
Product Width (unpacked)	220 mm
Product Depth (unpacked)	300 mm
Product Weight (unpacked)	21000 g

Fits to



R88M-1M11K015C-BS2

1S AC servo motor, 11 kW, 400 VAC, 1500 rpm, 70.0 Nm, absolute encoder, with brake



R88M-1M11K015C-S2

1S AC servo motor, 11 kW, 400 VAC, 1500 rpm, 70.0 Nm, absolute encoder



R88M-1M15K015C-BS2

1S AC servo motor, 15 kW, 400 VAC, 1500 rpm, 95.5 Nm, absolute encoder, with brake



R88M-1M15K015C-S2

1S AC servo motor, 15 kW, 400 VAC, 1500 rpm, 95.5 Nm, absolute encoder

CAD Library



1S series with SS1/SLS Safety Sub-Functions Brochure

EN PDF 1.81 MB



1S-series Servos for EN Instruction Manual

EN PDF 3.39 MB



1S-series servos with SS1/SLS safety functions Users Manual

EN PDF 28 MB



R88D-1SN_-ECT-51 Instruction Sheet

EN PDF 325 KB



R88M-1_R88D-1SN_-ECT-51 AC Servo Drives 1S-series Datasheet

EN PDF 9.42 MB