



USB interface can be activated

## Technical details

### General data

Approval: CE, UKCA, UL Recognized Component

### Technical data

#### Inputs

DC voltage at input: 24 V DC

Galv. isolation input: Yes

#### USB interface

Number of USB host interfaces: 1

Type of USB host interface: USB 2.0 Type A

### Environmental data

Climatic suitability to ...: EN 60068-2-2, EN 60068-2-1

Ambient temperature standard: EN 60068-2-14

Ambient temperature: -30 - 60 °C

Climatic suitability standard: EN 60068-2-78

Humidity rating: 93 % r. h. at 40 °C

Perm. operating height ASL: 2000 m

EMC to standard ...: EN 61131-2 (Zone B)

Vibration to standard ...: EN 60068-2-6

Acc. shock to standard1: 15g

Clearance & creepage dist. to: EN 61131-2

Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Protection type, housing:	IP20
<b>Mechanical data</b>	
Mounting position:	any
Max. cable length:	30 m
Connection terminal:	Spring-loaded terminal, plugin
Terminal style:	plug-in
Width dimension:	31.2 mm
Depth dimension:	55 mm
Net weight:	30 g
Gross weight:	67 g
<b>Environment</b>	
WEEE classification (08/2018):	5 devices (feed size < 50cm)
<b>Commercial data</b>	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371292
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002024
UNSPSC 25:	39122205
GTIN:	4046548103069
Volume:	0 dm3
Harmonized System Code:	85389099
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1