



Activatable Ethernet interfaces (RJ45), supply and input voltage 24 V

Technical details

General data

Approval: CE, UKCA, UL Recognized Component

Technical data

Electrical data

Supply voltage (V): 24 - 24 V

Type of supply voltage U1: DC

Power consumption DC: 0.48 W

Inputs

Number of inputs: 2

DC voltage at input: 24 V

Input type to EN 61131-2: 3

Galv. isolation input: No

Ethernet interface

Connector type ETHERNET int.: RJ45

Ethernet transmission rate: 10/100 Mbit/s

Number of Ethernet interfaces: 2

Environmental data

Climatic suitability to ...: EN 60068-2-2, EN 60068-2-1

Ambient temperature standard: EN 60068-2-14

Ambient temperature: -20 - 60 °C

Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Condensation permitted?:	Not permitted
Perm. operating height ASL:	2000 m
EMC to standard ...:	EN 61131-2 (Zone B)
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Clearance & creepage dist. to:	EN 61131-2
Overvoltage category:	II
Pollution degree clear.&creep.:	2
Protection type standard:	EN 60529
Protection type, housing:	IP20
Mechanical data	
Mounting position:	any
Max. cable length:	30 m
Connection terminal:	Spring-loaded terminal, plugin
Terminal style:	plug-in
Height dimension:	40 mm
Width dimension:	30 mm
Depth dimension:	59.2 mm
Net weight:	42 g
Gross weight:	60 g
Environment	
WEEE classification (08/2018):	6 small IT-/communic. device
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27371292
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000017

ETIM Reference Feature:	EC002024
UNSPSC 25:	39122205
GTIN:	4046548107555
Volume:	0.314 dm3
Harmonized System Code:	85176200
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1

Optional accessories



402325

PIT or DIN rail adapter