

PITreader sticker ye 5

402345



Transponder sticker for authentication system PITreader Card, authorisation for operating modes 1, 2, 3, 4 and 5 Colour: yellow Material: Plastic

Technical details

General data	
Approval:	CE, UKCA
Sensor principle:	Transponder
Technical data	
Environmental data	
Ambient temperature:	-25 - 50 °C
Climatic suitability standard:	EN 60068-2-78
Humidity rating:	93 % r. h. at 40 °C
Vibration to standard ...:	EN 60068-2-6
Acc. shock to standard1:	15g
Protection type, housing:	IP68
Mechanical data	
Mounting position:	any
Housing material:	PVC
Depth dimension:	0.8 mm
Net weight:	1 g
Gross weight:	2 g
Transponder	
Transponder energy supply:	Passive (battery-free)
Operating frequency:	13.56 MHz

Environment	
WEEE classification (08/2018):	0 not relevant
Commercial data	
ECLASS version:	ECLASS-13
ECLASS Reference Feature:	27280402
ETIM Version:	ETIM-9.0
ETIM Reference Group:	EG000026
ETIM Reference Feature:	EC002996
UNSPSC 25:	39122205
GTIN:	4046548105322
Volume:	0 dm3
Harmonized System Code:	85389099
Type of tariff number:	TARIC
Use of customs tariff number:	Ausfuhr, Einfuhr
Quantity per packaging unit:	1