



## NXR-CD166C-IL2

NXR Series IO-Hub IP67, 16 input/output, 8x M12 connectors

# Specifications

Type of module	IO-Hub
Communication port(s)	IO-Link
Number of digital inputs	16
Digital input type	PNP
Number of digital outputs	16
Digital output type	PNP
I/O connection type	M12
Number of I/O connectors	8
Product Height (unpacked)	174 mm
Product Width (unpacked)	62 mm
Product Depth (unpacked)	37.8 mm
Product Weight (unpacked)	280 g

# Accessories



**XS2W-D421-D81-F**

Cable with connectors on both cable ends, M12 straight socket (female), M12 straight plug (male), 4-poles, A coded, PVC fire-retardant robot cable, IP67, 2 m



**XS2W-D421-G81-F**

Cable with connectors on both cable ends, M12 straight socket (female), M12 straight plug (male), 4-poles, A coded, PVC fire-retardant robot cable, IP67, 5 m

**XS2Z-22**

Water-resistive cover for M12-female connector



**XS3W-M42C-4C2-A**

Cable with connectors on both cable ends, M8 straight socket (female), Smartclick M12 straight plug (male), 4-poles, PVC standard cable, IP67, 0.2 m



**XS5R-D426-1**

Y-Joint plug/socket M12 SmartClick without cable (4-4, 4-2)

## CAD Library



### EAC Mark removal Discontinuation Notice

EN PDF 221 KB




### IO-Link Series Brochure

EN PDF 6.41 MB



### NXR Series IP67 Remote Terminal Flyer

EN PDF 1.56 MB



### NXR-CD166C-IL2 IO-Link IODD file

EN ZIP 73.3 KB



### NXR-\_D166C-IL2 Datasheet

EN PDF 3.02 MB



### NXR-\_D166C-IL2 IO-Hub Users Manual

EN PDF 6.14 MB



### Sysmac Catalogue

EN PDF 43.5 MB



### Sysmac: A Fully Integrated Platform Brochure

EN PDF 19.1 MB