

SOLENOID OPERATED DIRECTIONAL CONTROL VALVES

Supplied with Industrial 22 mm operator - without solenoid

INTERNAL supply to operator valve(s) via port 1

Maximum operating pressure : 10 bar

Operating Temperature Range : -10°C to +50°C

Solenoid and plug/connector to be ordered separately



Symbol	Size	Actuation	Return	Min Operating Pressure (bar)	Changeover time (ms) at 6 bar @20°C actua./return	Weight Kg	Order code
3/2 valves. internal air. standard temperature							
	G1/8	Electric signal	Electric signal	1.5	10/10	0.31	P2LAX311EENDDN
	G1/4			1.5	10/12	0.31	P2LBX312EENDDN
	G3/8			1.5	17/17	0.41	P2LCX313EENDDN
	G1/2			1.5	17/17	0.41	P2LDX314EENDDN
	G1/8	Electric signal	Spring	3.2	18/40	0.31	P2LAX311ESNDDN
	G1/4			3.5	18/45	0.31	P2LBX312ESNDDN
	G3/8			3.5	25/75	0.40	P2LCX313ESNDDN
	G1/2			3.5	25/75	0.40	P2LDX314ESNDDN
5/2 valves. internal air. standard temperature							
	G1/8	Electric signal	Electric signal	1.5	9/9	0.16	P2LAX511EENDDN
	G1/4			1.5	10/10	0.31	P2LBX512EENDDN
	G3/8			1.5	13/13	0.41	P2LCX513EENDDN
	G1/2			1.5	13/13	0.41	P2LDX514EENDDN
	G1/8	Electric signal	Spring	3.2	12/38	0.16	P2LAX511ESNDDN
	G1/4			3.5	14/42	0.31	P2LBX512ESNDDN
	G3/8			3.5	16/60	0.40	P2LCX513ESNDDN
	G1/2			3.5	16/60	0.40	P2LDX514ESNDDN
5/3 valves. internal air. standard temperature							
	G1/8	Electric signal Closed centre position	Electric signal Self centring	3.5	15/40	0.17	P2LAX611EENDDN
	G1/4			3.5	18/50	0.33	P2LBX612EENDDN
	G3/8			3.5	20/65	1.00	P2LCX613EENDDN
	G1/2			3.5	20/70	1.00	P2LDX614EENDDN
	G1/8	Electric signal Pressurised centre position	Electric signal Self centring	3.5	15/40	0.17	P2LAX711EENDDN
	G1/4			3.5	18/50	0.33	P2LBX712EENDDN
	G3/8			3.5	20/65	1.00	P2LCX713EENDDN
	G1/2			3.5	20/70	1.00	P2LDX714EENDDN
	G1/8	Electric signal Vented centre position	Electric signal Self centring	3.5	15/40	0.17	P2LAX811EENDDN
	G1/4			3.5	18/50	0.33	P2LBX812EENDDN
	G3/8			3.5	20/65	1.00	P2LCX813EENDDN
	G1/2			3.5	20/70	1.00	P2LDX814EENDDN