



BATTERY-POWERED HYDRAULIC PUNCHING TOOL, BI-LINEAR, FOR HOLE PUNCHING SHEET MATERIALS UP TO 3,5 MM THICKNESS

INCLUDED INTO PACKAGE

• ASC55-UK: --	• CB1820L: LI-ION BATTERY
• TD-11: PULLER	• TD-19: PULLER

CERTIFICATIONS & APPROVALS

	CE		UKCA
---	----	---	------

Features

TECHNICAL INFORMATION

Range of operating temperature	-15 °C
Supply voltage	18 V
Pressure control system	max pressure valve
Mains power connection	type G
Depressurizing	manual
Power supply	Electrical motor (battery)
maximum drilling thickness	3.5 mm

WEIGHT AND DIMENSIONS

Net weight in operation	4 kg
Dimensions	467x126x79 mm
maximum rectangular drilling side 2	136 mm
maximum rectangular drilling side 1	72 mm
maximum square drilling side	138 mm
maximum round drilling diameters	140 mm

LOGISTIC

Unit in minimal packaging	1 PCE
Unit in standard packaging	1 PCE

CLASSIFICATION AND DATA ORDERING

Customs code	84672920
---------------------	----------

COMPATIBILITY

Supply configuration	2 x CB1820L battery; ASC30-36-UK battery charger; Ø11.5 mm spiral bit; TD-11 7/16" puller; TD-19 3/4" puller; USB cable; shoulder strap; VAL-M/X1 plastic case
-----------------------------	--

