



Certification Information

- * Certification Number BVS 22 ATEX E 032X
- * Certification Number IECEx BVS 22.0029X
- * Approved to (Gas) II 2G Ex db eb IIC T6 Gb
- * Approved to (Dust) II 2D Ex tb IIIC T80°C Db
- * Ingress Protection IP66 (EN60529)
- * Ambient Temperature Range -20°C to +40°C

Features

- * Chemical & impact resistant Polyamide enclosure
- * Maximum switch rating of 6A AC15 230V
- * Maximum switch rating of 6A DC13 24V
- * 1 x M20 entry as standard (unless stated)
- * Custom built assemblies are available
- * Enclosure dimensions 125 x 85 x 77.5mm



GHG41182/SJ21



GHG41182/SJ3-4NC

2 Gang Control Stations (Zone 1 & Zone 21)

Part Number	Description	Function	Accessory	Contacts / Voltage	Action	
GHG41182/SJ20	Push Button Station	START	START & Green Inserts	1NO + 1NC	Momentary	
		STOP	STOP & Red Inserts			
GHG41182/SJ21	Momentary Start Push Button Station With Emergency Stop	START	START & Green Inserts			
		Emergency Stop	-		Pull To Reset	
GHG41182/SJ21X		START	START & Green Inserts		Momentary	
		Emergency Stop	Padlock Bracket		Pull To Reset	
GHG41182/SJ22F	Momentary Start Push Button Station With Process Stop	START	START & Green Inserts		Momentary	
		Process Stop	Painted Flap Cover		Pull To Reset	
GHG41182/SJ23R-G	Double Push Button START & STOP Station	Visual Indication	Red & Green Lens		20 - 250V AC / DC	
		START / STOP	START, STOP, Green & Red Inserts		1NO + 1NC	Momentary

Zone 0



Zone 1



Zone 2



Zone 20



Zone 21



Zone 22



IEC Ex



Emergency Stop Control Stations With 4 Pole Contact Block (Zone 1 & Zone 21)

Part Number	Description	Function	Accessory	Contacts / Voltage	Action
GHG41182/SJ3-4	Emergency Stop Station	Emergency Stop	-	2NO + 2NC	Pull To Reset
GHG41182/SJ3-4NC			-	4NC	
GHG41182/SJ3GS-4NC			Yellow Inadvertent Shroud		



Use certified Ex cable glands suitable for the cable type and enclosure. Fit serrated washers and locknuts where metal glands are installed into Exe enclosures with clearance holes (section 4.5.4 of the CompEx Guide). Only one adaptor or reducer is recommended per entry. Seal unused entries with certified stopping plugs. All accessories are available from stock.