



SZ40

- Suitable for mounting inside and outside of the hazardous area
- To prevent inadvertent closing, e.g. during maintenance
- For complex plant
- Prevents actuation of the switch
- Lockout tag with 6 circular holes

Data

General data

Material of the operators	Plastic, glass-fibre reinforced thermoplastic
Colour of the housing	Red
Colour of the operating element	Black
Gross weight	69 g
Material of the holder	Glass-fibre, reinforced thermoplastic
Colour of the holder	Black

Mechanical data

Type of the fixing screws	2x M5
Type of the screw head	Flat head screw

Mechanical data - Dimensions

Length	109 mm
Width	19 mm
Height	12 mm
Diameter hole	6 mm

Pictures

Product picture (catalogue individual photo)




ID: kaz40f59

| 168.62 KB | .jpg | 999 x 1499 Pixel

| 17.07 KB | .jpg | 233 x 350 Pixel

| 22.07 KB | .png | 209 x 314 Pixel

Dimensional drawing basic component




ID: ksz40g04

| 38.91 KB | .jpg | 1000 x 461 Pixel

| 2.22 KB | .png | 210 x 97 Pixel

Dimensional drawing basic component




ID: ksz40g03

| 66.01 KB | .jpg | 1000 x 291 Pixel

| 3.84 KB | .png | 210 x 61 Pixel

Dimensional drawing basic component



ID: ksz40g05

| 34.41 KB | .jpg | 1000 x 214 Pixel

| 2.25 KB | .png | 210 x 45 Pixel

Assembly example



ID: kaz40f56

| 295.82 KB | .jpg | 999 x 1499 Pixel

| 26.45 KB | .jpg | 233 x 350 Pixel

| 45.41 KB | .png | 209 x 314 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/06/2026, 11:59