




Rotation Speed Monitor KFU8-DW-1.D

- Speed monitoring up to 40 kHz
- 1 pre-select value with relay output and LED indicator
- 2-, 3-, 4-wire and NAMUR sensors as well as rotary encoder connectable
- Start-up delay
- Menu driven operation via 4 front keys
- Period measurement
- Output signal can be inverted
- Display devices can be set between 0.1 ... 2.5 sec.

Rotation Speed Monitor



Technical Data

Functional safety related parameters

MTTF _d	100 a
-------------------	-------

Supply

Rated voltage	U _r	196 ... 250 V AC , 98 ... 127 V AC , 50/60 Hz 20 ... 30 V DC
Fusing		external fusing 4 A
Power consumption		AC: < 5 VA DC: < 5 W

Input 1

Connection	terminals 8-, 9+
Connectable sensor types	NAMUR sensors according to DIN EN 60947-5-6
Open loop voltage	8.2 V DC
Short-circuit current	6.5 mA
Switching point	1.2 ... 2.1 mA Switching hysteresis approx. 0.2 mA
Input frequency	0.002 ... 10000 Hz, pulse length/duration: ≥ 20µs
Impedance	1.2 kΩ

Input 2

Switching point	high: 16 ... 30 V DC; max. 10 mA due to integrated constant current sink; R _i ≈ 3 kΩ low: 0 ... 6 V DC
Input frequency	0.002 ... 40000 Hz, pulse length/duration: ≥ 12µs
Connection	terminals 7+, 13- sensor supply terminals 14, 15 NPN/PNP input (galvanically isolated)
Connectable sensor types	2-, 3-, or 4-wire proximity sensor, incremental rotary encoder, or externally generated pulses 16 ... 30 V
Sensor supply	19 ... 31 V DC non-stabilised; ≤ 30 mA short-circuit protected

Input 3

Sensor supply	24 V DC ± 10 %, 30 mA , short-circuit protected
Start-up override	Triggering by external signal 16 ... 30 V or Place jumper between terminals 2/3 or by switching on supply voltage (terminal 2 and terminal 3 permanently bridged)
Hold-up time	0.1 ... 999.9 s (External trigger signal)

Output

Relay	1 changeover contact NO, NC, COM
Contact loading	250 V AC/2 A/ cos φ ≥ 0.7 40 V DC/2 A
Delay	≤ 20 ms (incl. calculation time)
Mechanical life	≥ 20.000.000 switching cycles

Release date: 2025-06-13 Date of issue: 2025-06-18 Filename: 190149_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com

USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

 **PEPPERL+FUCHS**

Technical Data

Transfer characteristics

Changing interval	5 ms (Internal processing time)
Time delay before availability	≤ 400 ms
Measuring error	0 ... 40000 Hz: ≤ ±0,10% Display: ±1 digit
Timer function	ON-delay, OFF-delay, one shot, pulse extension
Time	0 ... 999.9 s ; mode of operation reversible

Standard conformity

Electromagnetic compatibility	acc. to EN 50081-2 / EN 50082-2
-------------------------------	---------------------------------


Ambient conditions

Ambient temperature	-25 ... 40 °C (-13 ... 104 °F)
Storage temperature	-40 ... 85 °C (-40 ... 185 °F)
Relative humidity	max. 80 %, not condensing
Altitude	0 ... 2000 m
Operating conditions	The device has only to be used in an indoor area.

Mechanical specifications

Connection assembly	Caution: Please be aware that the device may only be connected to a switchable power supply. The switch or circuit breaker must be easy to reach and identified as the separator for the device.
Degree of protection	IP20
Connection	coded, removable terminals , max. core cross section 0.34 ... 2.5 mm ²
Construction type	modular terminal housing in Makrolon, System KF For use in the switch cabinet/switch cabinet module
Mounting	snap-on to 35 mm standard rail or screw fixing

Connection



Release date: 2025-06-13 Date of issue: 2025-06-18 Filename: 190149_eng.pdf

Refer to "General Notes Relating to Pepperl+Fuchs Product Information".

Pepperl+Fuchs Group
www.pepperl-fuchs.com


USA: +1 330 486 0001
fa-info@us.pepperl-fuchs.com

Germany: +49 621 776 1111
fa-info@de.pepperl-fuchs.com

Singapore: +65 6779 9091
fa-info@sg.pepperl-fuchs.com

PEPPERL+FUCHS

Assembly



Release date: 2025-06-13 Date of issue: 2025-06-18 Filename: 190149_eng.pdf

Additional Information

Device description

The KFU8-DW-1.D Speed Monitor is a device for the **indication and monitoring of periodic signals**, which occur in almost all areas of automation and process technology, i. e. of frequencies in general and rotational speeds in special cases. The input signals are evaluated in accordance with the cycle method, i. e. by measurement of the period of oscillation and conversion into frequency or rotational speed by a very fast μ controller.

The frequently occurring special case of rotational speed measurement has been paid particular attention in the development of the device. Thus **indication** and **input** can be either in **Hz** or in **rpm**. It is also possible, in applications involving slow processes, in which the signal sensors **provide many pulses per revolution**, to operate automatically with the **actual rotational speed** of the drive by specifying the number of pulses per revolution.

The indication of the measured value is provided on a **4-digit, 7-segment LED display** on the front of the device, with **up to 3 places after the decimal point**.

The monitoring function is achieved on the basis of a **limit value**, whose upper and lower hysteresis value is freely selectable within the respective display range.

The **output signal** is generated by a relay with a changeover contact, when the hysteresis limits are violated. Thanks to a high switching capability, the relay output can **be used for the direct activation** of an actuating element or **as an input signal for a higher level control system**.

Also, the switching status of the relay is indicated by means of a **yellow LED** on the front of the device.

A function block is connected in series with the relay, which **10 provides for various timer functions** and thus obviates the requirement for the subsequent addition of a timer relay. In addition to the **pull-in and drop-out delay, passing make contact and pulse extension**, the **direction of operation of the relay**, i. e. monitoring of speed fluctuation about a nominal value, can also be selected.

The built-in **start-up override**, initiated when the power supply is switched on, or by an external signal, **prevents error signals** during the running up of the monitored system.


The speed monitor can be supplied with **115 V AC, 230 V AC or by a 24 V DC** supply and when connected to an alternating voltage it provides a **24 V DC source to supply the signal sensor**.

All current **two, three and four-wire proximity switches** and incremental **encoders** can be accepted as the signal sensor. In addition, two terminals are reserved for the connection of **proximity switches in accordance with DIN 19234 (NAMUR)**.

Terminal assignment

T. 1:	Signal sensor supply GND
T. 2:	Trigger input for start-up override
T. 3:	Signal sensor supply +24 V DC
T. 4:	Power supply + 24 V DC
T. 5:	Power supply GND
T. 6:	Not connected.
T. 7:	Signal sensor supply +24 V DC
T. 8:	NAMUR input L-
T. 9:	NAMUR input L+
T. 10:	Relay make contact, NO
T. 11:	Relay break contact, NC
T. 12:	Relay root, COM
T. 13:	Signal sensor supply GND
T. 14:	Signal sensor NPN input
T. 15:	Signal sensor PNP input
T. 16:	Power supply L1, 230 V AC
T. 17:	Power supply L1, 115 V AC
T. 18:	Power supply N

Timer functions, reversal of operating direction of the output relay



Operating principle

Release date: 2025-06-13 Date of issue: 2025-06-18 Filename: 190149_eng.pdf

