



E32-LT11N 2M

Fiber optic sensor head, retro-reflective, long distance detection, M4 hexagonal back, right-angled head, integrated lens, R2
flexible fiber, 2 m cable

Specifications

Sensing method	Through-beam
Shape	Threaded
Size	M4
Application	Long distance detection
Features	90° cable exit, Built-in lens, Flexible fiber, Hexagonal back
Temperature range	-40-70 °C
Sensing distance	4000 mm
Cable length	2 m
Sleeve diameter	8888 mm
Sleeve length	8888 mm
Bending radius	2 mm
Free cut	✓
Material core	Plastic
Degree of protection (IP)	IP50
Sensing surface orientation	Right-angle
Material sheath	Polyethylene

Related products



E3X-ZV and E3X-MZV
Smart Fiber Amplifier



E3NX-CA
High-performance color
mark sensor



E3NX-CA
High-performance color
mark sensor



E3NX-MA
Smart Fiber Amplifier Units



E3X-NA
Digital fiber amplifier with
potentiometer adjustment



E3NX-FA
High-performance digital
fiber amplifier

Downloads

CAD Library



**E32-LT/LD Hex-shaped
Fiber Unit**
Brochure

EN PDF 6.35 MB



Fiber Sensor Selection
Selection Guide

EN PDF 15.9 MB

