



RSS16-D-R-ST8H

- Universal coding with RFID technology
- 1 x connector plug M12, 8-pole
- Series-wiring unlimited
- with latching
- Door stop with magnetic latching
- Thermoplastic enclosure
- RFID-technology for needs-based protection against tampering
- 3 different directions of actuation
- Connection terminal or plug connection
- Suitable for series-wiring

Data

Approvals - Standards

Certificates	cULus
	TÜV
	IC
	FCC
	ANATEL

General data

Standards	EN IEC 60947-5-3
Coding	Universal coding
Coding level according to EN ISO 14119	Low
Working principle	RFID
Housing construction form	Block
Installation conditions (mechanical)	not flush
Sensor topology	Sensor for series wiring
Housing material	Plastic, glass-fibre reinforced thermoplastic, self-extinguishing
Active area	Glass-fibre, reinforced thermoplastic
Reaction time, maximum	100 ms
Duration of risk, maximum	200 ms

General data

Gross weight	250 g
--------------	-------

General data - Features

Latching magnet	Yes
-----------------	-----

Diagnostic output	Yes
-------------------	-----

Short circuit detection	Yes
-------------------------	-----

Cross-circuit detection	Yes
-------------------------	-----

Series-wiring	Yes
---------------	-----

Safety functions	Yes
------------------	-----

Cascadable	Yes
------------	-----

Integral system diagnostics, status	Yes
-------------------------------------	-----

Number of LEDs	2
----------------	---

Number of semi-conductor outputs with signaling function	1
--	---

Number of fail-safe digital outputs	2
-------------------------------------	---

Safety classification

Standards	EN IEC 61508
-----------	--------------

	EN ISO 13849-1
--	----------------

Performance Level, up to	e
--------------------------	---

Category	4
----------	---

PFH value	$6.30 \times 10^{-11} / \text{h}$
-----------	-----------------------------------

PFD value	1.50×10^{-5}
-----------	-----------------------

Safety Integrity Level (SIL), suitable for applications in	3
--	---

Mission time	20 Year(s)
--------------	------------

Mechanical data

Actuating panels	from head
------------------	-----------

	front side
--	------------

	rear
--	------

Active area	front side
-------------	------------

	cover-side
--	------------

	lateral
--	---------

Mounting	2 x M5, Cylinder head screw
----------	-----------------------------

Mechanical data

Tightening torque of the fixing screws	2 Nm
--	------

Mechanical data - Switching distances

Switch distance, typical	15 mm
Assured switching distance "ON" Sao	5 mm
Assured switching distance "OFF" Sar	30 mm
Note (switching distance)	All switching distances in accordance EN IEC 60947-5-3
Hysteresis (Switching distance), maximum	2 mm
Repeat accuracy R	0.5 mm

Mechanical data - Connection technique

Note (length of the sensor chain)	Cable length and cross-section change the voltage drop depending on the output current
Note (series-wiring)	Unlimited number of devices, observe external line fusing, max. 31 devices in case of serial diagnostic SD
Cable entry	M12 (A-coding)
Termination	Connector M12, 8-pole
Cable section, minimum	0.25 mm ²
Cable section, maximum	1.5 mm ²

Mechanical data - Dimensions

Length of sensor	91 mm
Width of sensor	52 mm
Height of sensor	30 mm

Ambient conditions

IP Degree of protection	IP66
	IP67
	IP65
Ambient temperature	-28 ... +70 °C
Storage and transport temperature	-28 ... +85 °C
Relative humidity, maximum	93 %
Note (Relative humidity)	non-condensing
	non-icing
Resistance to shock	30 g / 11 ms

Ambient conditions

Permissible installation altitude above sea level, maximum	2,000 m
--	---------

Ambient conditions - Insulation values

Rated insulation voltage U_i	32 VDC
Rated impulse withstand voltage U_{imp}	0.8 kV
Overvoltage category	III
Degree of pollution	3

Electrical data

Operating voltage	24 VDC -15 % / +10 %
Operating current, minimum	0.5 mA
No-load supply current I_0 , typical	100 mA
Rated operating voltage	24 VDC
Operating current	2,100 mA
Required rated short-circuit current	100 A
Time to readiness, maximum	2,000 ms
Switching frequency, maximum	1 Hz

Electrical data - Safety digital inputs

Current consumption of the safety inputs	5 mA
--	------

Electrical data - Safety digital outputs

Rated operating current (safety outputs)	1,000 mA
Output current, (fail-safe output), maximum	1 A
Design of control elements	p-type
Voltage drop U_d , maximum	1 V
Leakage current I_r , maximum	0.5 mA
Voltage, Utilisation category DC-12	24 VDC
Current, Utilisation category DC-12	1 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	1 A

Electrical data - Diagnostic outputs

Operating current	50 mA
-------------------	-------

Electrical data - Diagnostic outputs

Design of control elements	p-type
Voltage drop U_d , maximum	2 V
Voltage, Utilisation category DC-12	24 VDC
Current, Utilisation category DC-12	0.05 A
Voltage, Utilisation category DC-13	24 VDC
Current, Utilisation category DC-13	0.05 A

Electrical data - Electromagnetic compatibility (EMC)


Interfering radiation	IEC 61000-6-4
-----------------------	---------------

Status indication

Note (LED switching conditions display)	LED green: Supply voltage
	Multi-coloured LED: Green, Red
	LED red: Fault
	LED yellow: Operating condition

Pictures

Product picture (catalogue individual photo)




ID: krss1f03

| 1,018.18 KB | .jpg | 1000 x 2139 Pixel

| 35.28 KB | .jpg | 164 x 350 Pixel

| 133.82 KB | .png | 210 x 449 Pixel

Dimensional drawing basic component




ID: krss1g01

| 141.14 KB | .jpg | 1000 x 762 Pixel


| 4.73 KB | .png | 210 x 160 Pixel

Wiring example




ID: krss1l02
[| 101.19 KB | .jpg | 1000 x 701 Pixel](#)

Wiring example



ID: krss1l03
[| 112.09 KB | .jpg | 1000 x 520 Pixel](#)

Contact arrangement



ID: km12-k8b
[| 138.62 KB | .jpg | 999 x 1184 Pixel](#)
[| 5.26 KB | .png | 209 x 248 Pixel](#)

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.
Generated on: 12/08/2026, 09:12