



## RSS16-I2-D-R-SK

- Thermoplastic enclosure
- RFID-technology for needs-based protection against tampering
- 3 different directions of actuation
- Door stop with magnetic latching
- Connection terminal or plug connection
- Suitable for series-wiring
- Repeated individual coding with RFID technology

### Data

#### Approvals - Standards

|              |        |
|--------------|--------|
| Certificates | cULus  |
|              | TÜV    |
|              | IC     |
|              | FCC    |
|              | ANATEL |

#### General data

|                                        |                                                                   |
|----------------------------------------|-------------------------------------------------------------------|
| Standards                              | EN IEC 60947-5-3                                                  |
| Coding                                 | Individual coding, multiple teaching                              |
| Coding level according to EN ISO 14119 | High                                                              |
| Working principle                      | RFID                                                              |
| Housing construction form              | Block                                                             |
| Installation conditions (mechanical)   | not flush                                                         |
| Sensor topology                        | Sensor for series wiring                                          |
| Housing material                       | Plastic, glass-fibre reinforced thermoplastic, self-extinguishing |
| Active area                            | Glass-fibre, reinforced thermoplastic                             |
| Reaction time, maximum                 | 100 ms                                                            |
| Duration of risk, maximum              | 200 ms                                                            |
| Gross weight                           | 250 g                                                             |

## General data - Features

|                                                          |     |
|----------------------------------------------------------|-----|
| Latching magnet                                          | Yes |
| Diagnostic output                                        | Yes |
| Short circuit detection                                  | Yes |
| Cross-circuit detection                                  | Yes |
| Series-wiring                                            | Yes |
| Safety functions                                         | Yes |
| Cascadable                                               | Yes |
| Integral system diagnostics, status                      | Yes |
| Number of LEDs                                           | 2   |
| Number of semi-conductor outputs with signaling function | 1   |
| Number of fail-safe digital outputs                      | 2   |

## Safety classification

|                                                            |                                   |
|------------------------------------------------------------|-----------------------------------|
| Standards                                                  | EN IEC 61508                      |
|                                                            | EN ISO 13849-1                    |
| Performance Level, up to                                   | e                                 |
| Category                                                   | 4                                 |
| PFH value                                                  | $6.30 \times 10^{-11} / \text{h}$ |
| PFD value                                                  | $1.50 \times 10^{-5}$             |
| Safety Integrity Level (SIL), suitable for applications in | 3                                 |
| Mission time                                               | 20 Year(s)                        |

## Mechanical data

|                                        |                             |
|----------------------------------------|-----------------------------|
| Actuating panels                       | from head                   |
|                                        | front side                  |
|                                        | rear                        |
| Active area                            | front side                  |
|                                        | cover-side                  |
|                                        | lateral                     |
| Mounting                               | 2 x M5, Cylinder head screw |
| Tightening torque of the fixing screws | 2 Nm                        |

### Mechanical data - Switching distances

|                                          |                                                        |
|------------------------------------------|--------------------------------------------------------|
| Switch distance, typical                 | 15 mm                                                  |
| Assured switching distance "ON" Sao      | 5 mm                                                   |
| Assured switching distance "OFF" Sar     | 30 mm                                                  |
| Note (switching distance)                | All switching distances in accordance EN IEC 60947-5-3 |
| Hysteresis (Switching distance), maximum | 2 mm                                                   |
| Repeat accuracy R                        | 0.5 mm                                                 |

### Mechanical data - Connection technique

|                                   |                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------|
| Note (length of the sensor chain) | Cable length and cross-section change the voltage drop dependiing on the output current                    |
| Note (series-wiring)              | Unlimited number of devices, observe external line fusing, max. 31 devices in case of serial diagnostic SD |
| Cable entry                       | 4 x M16 x 1,5                                                                                              |
| Termination                       | Screw terminals                                                                                            |
| Cable section, minimum            | 0.14 mm <sup>2</sup>                                                                                       |
| Cable section, maximum            | 1.5 mm <sup>2</sup>                                                                                        |

### Mechanical data - Dimensions

|                  |       |
|------------------|-------|
| Length of sensor | 91 mm |
| Width of sensor  | 52 mm |
| Height of sensor | 30 mm |

### Ambient conditions

|                                                            |                |
|------------------------------------------------------------|----------------|
| IP Degree of protection                                    | IP67           |
|                                                            | IP65           |
| Ambient temperature                                        | -28 ... +70 °C |
| Storage and transport temperature                          | -28 ... +85 °C |
| Relative humidity, maximum                                 | 93 %           |
| Note (Relative humidity)                                   | non-condensing |
|                                                            | non-icing      |
| Restistance to shock                                       | 30 g / 11 ms   |
| Permissible installation altitude above sea level, maximum | 2,000 m        |

### Ambient conditions - Insulation values

|                             |        |
|-----------------------------|--------|
| Rated insulation voltage Ui | 32 VDC |
|-----------------------------|--------|

### Ambient conditions - Insulation values

|                                      |        |
|--------------------------------------|--------|
| Rated impulse withstand voltage Uimp | 0.8 kV |
| Overvoltage category                 | III    |
| Degree of pollution                  | 3      |

### Electrical data

|                                      |                      |
|--------------------------------------|----------------------|
| Operating voltage                    | 24 VDC -15 % / +10 % |
| Operating current, minimum           | 0.5 mA               |
| No-load supply current I0, typical   | 100 mA               |
| Rated operating voltage              | 24 VDC               |
| Operating current                    | 2,100 mA             |
| Required rated short-circuit current | 100 A                |
| Time to readiness, maximum           | 2,000 ms             |
| Switching frequency, maximum         | 1 Hz                 |

### Electrical data - Safety digital inputs

|                                          |      |
|------------------------------------------|------|
| Current consumption of the safety inputs | 5 mA |
|------------------------------------------|------|

### Electrical data - Safety digital outputs

|                                             |          |
|---------------------------------------------|----------|
| Rated operating current (safety outputs)    | 1,000 mA |
| Output current, (fail-safe output), maximum | 1 A      |
| Design of control elements                  | p-type   |
| Voltage drop Ud, maximum                    | 1 V      |
| Leakage current Ir, maximum                 | 0.5 mA   |
| Voltage, Utilisation category DC-12         | 24 VDC   |
| Current, Utilisation category DC-12         | 1 A      |
| Voltage, Utilisation category DC-13         | 24 VDC   |
| Current, Utilisation category DC-13         | 1 A      |

### Electrical data - Diagnostic outputs

|                                     |        |
|-------------------------------------|--------|
| Operating current                   | 50 mA  |
| Design of control elements          | p-type |
| Voltage drop Ud, maximum            | 2 V    |
| Voltage, Utilisation category DC-12 | 24 VDC |
| Current, Utilisation category DC-12 | 0.05 A |

### Electrical data - Diagnostic outputs

|                                     |        |
|-------------------------------------|--------|
| Voltage, Utilisation category DC-13 | 24 VDC |
| Current, Utilisation category DC-13 | 0.05 A |

### Electrical data - Electromagnetic compatibility (EMC)

|                       |               |
|-----------------------|---------------|
| Interfering radiation | IEC 61000-6-4 |
|-----------------------|---------------|

### Status indication

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| Note (LED switching conditions display) | LED green: Supply voltage       |
|                                         | Multi-coloured LED: Green, Red  |
|                                         | LED red: Fault                  |
|                                         | LED yellow: Operating condition |


### Pictures

#### Product picture (catalogue individual photo)




ID: krss1f03  
| 1,018.18 KB | .jpg | 1000 x 2139 Pixel  
| 35.28 KB | .jpg | 164 x 350 Pixel  
| 133.82 KB | .png | 210 x 449 Pixel

#### Dimensional drawing basic component




ID: krss1g01  
| 141.14 KB | .jpg | 1000 x 762 Pixel  
| 4.73 KB | .png | 210 x 160 Pixel

#### Wiring example



ID: krss1l02  
| 101.19 KB | .jpg | 1000 x 701 Pixel

# Wiring example



ID: krss1l03  
| 112.09 KB | .jpg | 1000 x 520 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.  
Generated on: 12/08/2026, 09:29