



## RSS 36-I2-D-ST

- Repeated individual coding with RFID technology
- Coding level "High" according to ISO 14119
- 1 x connector socket M12, 8-pole
- Actuation from side
- Thermoplastic enclosure
- RFID-technology for needs-based protection against tampering
- Misaligned actuation possible
- 27 mm x 108.2 mm x 35 mm
- High repeat accuracy of the switching points
- 2 short-circuit proof PNP safety outputs
- Integral cross-short, wire-breakage and external voltage monitoring of the safety cables up to the control cabinet

### Data

#### Approvals - Standards

Certificates

cULus

TÜV

IC

ECOLAB

FCC

ANATEL

#### General data

Standards

EN IEC 60947-5-3

EN IEC 61508

EN ISO 13849-1

Coding

Individual coding, multiple teaching

Coding level according to EN ISO 14119

High

Working principle

RFID

Frequency band RFID

125 kHz

Transmitter output RFID, maximum

-6 dBm

Housing construction form

Block

## General data

|                                                                        |                                       |
|------------------------------------------------------------------------|---------------------------------------|
| Installation conditions (mechanical)                                   | not flush                             |
| Sensor topology                                                        | Sensor for series wiring              |
| Housing material                                                       | Glass-fibre, reinforced thermoplastic |
| Reaction time, maximum                                                 | 100 ms                                |
| Duration of risk, maximum                                              | 200 ms                                |
| Reaction time, switching off safety outputs via actuator, maximum      | 100 ms                                |
| Reaction time, switching off safety outputs via safety inputs, maximum | 0.5 ms                                |
| Gross weight                                                           | 80 g                                  |

## General data - Features

|                                                          |     |
|----------------------------------------------------------|-----|
| Diagnostic output                                        | Yes |
| Short circuit detection                                  | Yes |
| Cross-circuit detection                                  | Yes |
| Series-wiring                                            | Yes |
| Safety functions                                         | Yes |
| Cascadable                                               | Yes |
| Integral system diagnostics, status                      | Yes |
| Number of LEDs                                           | 3   |
| Number of semi-conductor outputs with signaling function | 1   |
| Number of fail-safe digital outputs                      | 2   |

## Safety classification

|                                                            |                                   |
|------------------------------------------------------------|-----------------------------------|
| Standards                                                  | EN IEC 61508                      |
|                                                            | EN ISO 13849-1                    |
| Performance Level, up to                                   | e                                 |
| Category                                                   | 4                                 |
| PFH value                                                  | $2.70 \times 10^{-10} / \text{h}$ |
| PFD value                                                  | $2.10 \times 10^{-5}$             |
| Safety Integrity Level (SIL), suitable for applications in | 3                                 |
| Mission time                                               | 20 Year(s)                        |

## Mechanical data

|                                                 |                                                                                                                                                                                                                  |
|-------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Actuating panels                                | lateral                                                                                                                                                                                                          |
| Active area                                     | lateral                                                                                                                                                                                                          |
| Mechanical lifetime, minimum                    | 1,000,000 Operations                                                                                                                                                                                             |
| Note (Mechanical lifetime)                      | Actuating speed < 0.25 m/s                                                                                                                                                                                       |
|                                                 | Operations for door weights $\leq 5$ kg                                                                                                                                                                          |
| Mounting                                        | A screw length of 25 mm is sufficient for sensor mounting and for side mounting of the actuators. 30 mm long screws are recommended when the actuator is mounted upright and/or when the sealing discs are used. |
| Type of the fixing screws                       | 2x M4 (cylinder head screws with washers DIN 125A / form A)                                                                                                                                                      |
| Tightening torque of the fixing screws, minimum | 2.2 Nm                                                                                                                                                                                                           |
| Tightening torque of the fixing screws, maximum | 2.5 Nm                                                                                                                                                                                                           |

## Mechanical data - Switching distances

|                                          |                                                                                                                                                                                                                                                                     |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switch distance, typical                 | 12 mm                                                                                                                                                                                                                                                               |
| Assured switching distance "ON" Sao      | 10 mm                                                                                                                                                                                                                                                               |
| Assured switching distance "OFF" Sar     | 20 mm                                                                                                                                                                                                                                                               |
| Note (switching distance)                | All switching distances in accordance EN IEC 60947-5-3                                                                                                                                                                                                              |
| Hysteresis (Switching distance), maximum | 2 mm                                                                                                                                                                                                                                                                |
| Repeat accuracy R                        | 0.5 mm                                                                                                                                                                                                                                                              |
| Note (Repeat accuracy R)                 | Axial offset: The long side allows for a maximum height misalignment (x) of sensor and actuator of 8 mm (e.g. mounting tolerance or due to guard door sagging). The axial misalignment (y) is max. $\pm 18$ mm (see figure: Operating principle). Minimum clearance |

## Mechanical data - Connection technique

|                                   |                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------|
| Note (length of the sensor chain) | Cable length and cross-section change the voltage drop depending on the output current                     |
| Note (series-wiring)              | Unlimited number of devices, observe external line fusing, max. 31 devices in case of serial diagnostic SD |
| Termination                       | Connector M12, 8-pole                                                                                      |

## Mechanical data - Dimensions

|                  |          |
|------------------|----------|
| Length of sensor | 22 mm    |
| Width of sensor  | 106.3 mm |
| Height of sensor | 25 mm    |

## Ambient conditions

|                                                            |                              |
|------------------------------------------------------------|------------------------------|
| IP Degree of protection                                    | IP69                         |
|                                                            | IP67                         |
|                                                            | IP65                         |
| Ambient temperature                                        | -28 ... +70 °C               |
| Storage and transport temperature                          | -28 ... +85 °C               |
| Relative humidity, maximum                                 | 93 %                         |
| Note (Relative humidity)                                   | non-condensing               |
|                                                            | non-icing                    |
| Resistance to vibrations                                   | 10 ... 55 Hz, amplitude 1 mm |
| Resistance to shock                                        | 30 g / 11 ms                 |
| Protection class                                           | III                          |
| Permissible installation altitude above sea level, maximum | 2,000 m                      |

## Ambient conditions - Insulation values

|                                           |        |
|-------------------------------------------|--------|
| Rated insulation voltage $U_i$            | 32 VDC |
| Rated impulse withstand voltage $U_{imp}$ | 0.8 kV |
| Overvoltage category                      | III    |
| Degree of pollution                       | 3      |

## Electrical data

|                                        |                                                     |
|----------------------------------------|-----------------------------------------------------|
| Operating voltage                      | 24 VDC -15 % / +10 % (stabilised PELV power supply) |
| Operating current, minimum             | 0.5 mA                                              |
| No-load supply current $I_0$ , typical | 35 mA                                               |
| Rated operating voltage                | 24 VDC                                              |
| Operating current                      | 600 mA                                              |
| Required rated short-circuit current   | 100 A                                               |
| Time to readiness, maximum             | 2,000 ms                                            |
| Switching frequency, maximum           | 1 Hz                                                |
| Electrical fuse rating, maximum        | 2 A                                                 |

## Electrical data - Safety digital inputs

|                                          |           |
|------------------------------------------|-----------|
| Designation, Safety inputs               | X1 and X2 |
| Current consumption of the safety inputs | 5 mA      |
| Test pulse duration, maximum             | 1 ms      |

### Electrical data - Safety digital inputs

|                                   |        |
|-----------------------------------|--------|
| Test pulse interval, minimum      | 100 ms |
| Classification ZVEI CB24I, Sink   | C1     |
| Classification ZVEI CB24I, Source | C1     |
|                                   | C2     |
|                                   | C3     |

### Electrical data - Safety digital outputs

|                                             |                             |
|---------------------------------------------|-----------------------------|
| Designation, Safety outputs                 | Y1 and Y2                   |
| Rated operating current (safety outputs)    | 250 mA                      |
| Output current, (fail-safe output), maximum | 0.25 A                      |
| Design of control elements                  | short-circuit proof, p-type |
| Voltage drop $U_d$ , maximum                | 1 V                         |
| Leakage current $I_r$ , maximum             | 0.5 mA                      |
| Voltage, Utilisation category DC-12         | 24 VDC                      |
| Current, Utilisation category DC-12         | 0.25 A                      |
| Voltage, Utilisation category DC-13         | 24 VDC                      |
| Current, Utilisation category DC-13         | 0.25 A                      |
| Test pulse interval, typical                | 1,000 ms                    |
| Test pulse duration, maximum                | 0.3 ms                      |
| Classification ZVEI CB24I, Source           | C2                          |
| Classification ZVEI CB24I, Sink             | C1                          |
|                                             | C2                          |

### Electrical data - Diagnostic outputs

|                                     |                             |
|-------------------------------------|-----------------------------|
| Designation, Diagnostic outputs     | OUT                         |
| Design of control elements          | short-circuit proof, p-type |
| Voltage drop $U_d$ , maximum        | 2 V                         |
| Voltage, Utilisation category DC-12 | 24 VDC                      |
| Current, Utilisation category DC-12 | 0.05 A                      |
| Voltage, Utilisation category DC-13 | 24 VDC                      |
| Current, Utilisation category DC-13 | 0.05 A                      |

### Electrical data - Electromagnetic compatibility (EMC)

|                       |               |
|-----------------------|---------------|
| Interfering radiation | IEC 61000-6-4 |
|-----------------------|---------------|

## Status indication

|                                         |                                 |
|-----------------------------------------|---------------------------------|
| Note (LED switching conditions display) | LED green: Supply voltage       |
|                                         | LED red: Fault                  |
|                                         | LED yellow: Operating condition |

## Pin assignment

|       |                                |
|-------|--------------------------------|
| PIN 1 | 1A1 Ue: (1)                    |
| PIN 2 | X1 Safety input 1              |
| PIN 3 | A2 GND Blue                    |
| PIN 4 | Y1 Safety output 1 Black       |
| PIN 5 | OUT Diagnostic output OUT Grey |
| PIN 6 | X2 Safety input 2 violet       |
| PIN 7 | Y2 Safety output 2 red         |
| PIN 8 | IN without function Pink       |

## Note

|                |                                                                                                                                                                                                                                                                     |
|----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Note (General) | Anforderungen an die Auswertung: Zweikanaliger Sicherheitseingang, geeignet für p-schaltende Sensoren mit Schließerfunktion. Die Funktionstests der Sensoren mit zyklischem Abschalten der Sensorausgänge für max. 1 ms müssen von der Auswertung toleriert werden. |
|                | Teaching of the individual coding of a RST actuator through a simple routine during start-up (as -I1). A protected coding process enables teaching a new actuator in case of maintenance.                                                                           |

## Pictures

### Product picture (catalogue individual photo)




ID: krss3f11

[| 501.72 KB | .jpg | 556 x 1624 Pixel](#)

[| 24.27 KB | .jpg | 120 x 350 Pixel](#)

[| 106.33 KB | .png | 210 x 613 Pixel](#)

## Dimensional drawing basic component




ID: 1rss3g03

| 124.22 KB | .jpg | 1000 x 695 Pixel

| 8.8 KB | .png | 210 x 146 Pixel

## Contact arrangement




ID: km12-k8b

| 138.62 KB | .jpg | 999 x 1184 Pixel

| 5.26 KB | .png | 209 x 248 Pixel

## Operating principle



ID: krss3a01

| 182.57 KB | .jpg | 1000 x 2610 Pixel

| 4.21 KB | .png | 210 x 548 Pixel

The details and data referred to have been carefully checked. Images may diverge from original. Further technical data can be found in the manual. Technical amendments and errors possible.

Generated on: 12/08/2026, 11:06